



Models:
 TC21: 21,000BTU/HR
 TC25: 25,000BTU/HR
 TC32*: 32,000BTU/HR
 TC25-3*: 25,000BTU/HR
 * 3 hose model for special orders



Titan-Cool

Industrial Air Conditioner

Typical Applications

- Portable air conditioning
- Computer rooms
- Industrial Kitchens
- Hospitals
- Disaster relief
- Vessels
- Multi-workstations
- Sports rooms
- Process cooling
- Equipment spot cooling
- Multiple factory offices
- Temporary office - lobby cooling
- Military Uses - tents, aircraft hangars
- Emergency cooling
- Laboratories
- Special events - marquee cooling



12 Litre condensate tank



TC32- 32,000 Btu/h
3 Hose model



Control Panel



TC-Cowl (Please note this accessory is sold separately)

The Titan-Cool provides spot cooling for large areas where cooling of the entire area is not feasible.

This Air Conditioner can also be used in smaller areas, with the room cooling thermostatically controlled feature.

The condenser air exhaust duct can be extended up to 9 metres.

TC21 & TC25 Operate on a 13 Amp BS approved UK plug
 TC32 Operates on a 20 Amp C-Form Plug



Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



COWL SPECIFICATION

TC32	
TC-Cowl32 (H x Bottom x Top diameters) cm	50x50x35
TC-Cowl32 Box Dimensions (HxWxD)cm	54.5x54.5x54.5
Cowl NW kg	5.5
Cowl GW kg	6.5
TC21 & TC25	
TC-Cowl (H x Bottom x Top diameters) cm	50x45x30
TC-Cowl Box Dimensions (HxWxD)cm	54.5x46.5x46.5
Cowl NW kg	5
Cowl GW kg	6

Titan-Cool

Industrial Air Conditioner

SPECIFICATION

Model	TITAN-COOL TC21	TITAN-COOL TC25*	TITAN-COOL TC32
Barcode	5038973003990	5038973003938	5038973004560
Features			
Cooling capacity (kw)	6.1	7.3	9.4
Cooling capacity (btu/h)	21000	25000	32000
Heating capacity (kw)	-	-	-
Cooling capacity (btu/h)	-	-	-
Dehumidifying capacity max Litres/day 30°C/R.H. 80%	45	46	55
Thermostatic control	✓	✓	✓
Fan speed settings (fan only setting)	2	2	2
Control panel	Electronic	Electronic	Electronic
Operating temperatures °C	18-45	18-45	18-45
Adjustable louvres	-	-	-
Fully assembled	✓	✓	✓
Condensate / Tank capacity Litres	12	12	12
Continuous drain option	-	-	-
Timer (hours)	-	-	-
Remote control	-	-	-
Fan blades	-	-	-
Built-in carry handle	-	-	-
Cable storage	-	-	-
Fitted wheels	✓	✓	✓
Specification			
Room Capacity (m ²)	50	60	76
Outside Diameter of Exhaust Duct (mm)	300	300	350
Exhaust duct can be extended to (metres)	9 (Not Sold With Unit)	9 (Not Sold With Unit)	9 (Not Sold With Unit)
Energy Efficiency Rating	B	B	B
Colour finish	Silver/Blue	Silver/Blue	Silver/Blue
Metal blades	-	-	-
Main body material	Metal	Metal	Metal
Power - Max (W)	2410	2600	4000
Voltage (V)	220-240V	220-240V	220-240V
Frequency (Hz)	50	50	50
Protection class I or II	I	I	I
Refrigerant charge	R410a/ 1.0kg	R410a/ 1.2kg	R410a/ 1.7kg
Plug Amp (A)	13	13	20
Airflow (m ³ /minute- max)	13.5	15.5	16.9
Noise level dB(A)	65	68	72.5
Net weight - product (kg)	93	98	109
Gross weight - retail box (kg)	95	100	111
Gross weight - outer carton (kg)	-	-	-
Product dimensions - H x W x D cm	124x56x62	124x56x62	135x56x70
Retail box dimensions - H x W x D cm	118x59x65	118x59x65	126x59x69
All Prem-Air products are RoHS compliant and carry the WEEE Directive logo			

Due to continuous research and development the specifications are subject to change without notice.

* Available with 3 hoses for container orders (TC25-3)

Get In Touch

Call: 0845 6880112
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH