

GP RANGE: MANUAL AND AUTOMATIC MOBILE LPG DIRECT FIRED SPACE HEATERS

MAXIMUM PERFORMANCE MINIMUM CONSUMPTION





www.biemmedue.com





PROFESSIONAL QUALITY FOR ALL APPLICATIONS

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV =ISO 9001/2000=



Get In Touch

Call: <u>0845 6880112</u>

Email: info@adremit.co.uk

Our Address







ARCOTHERM SPACE HEATERS OF THE GP RANGE PROVIDE IMMEDIATE AND ECONOMICAL HEAT.

Manual (GP/M) or automatic (GP/A), ceiling mounted or transportable, they can be widely used in building sites, greenhouses, animal rearing facilities, and in any case in ventilated premises, for drying, thawing and heating. Direct LPG-fired GP space generators are also ideal for carbon dioxide fertilizing of protected crops. Versatile and reliable, they are easy to use and safe thanks to the control devices which, in the case of malfunctioning, cut out the motor.

HEATING EFFICIENCY

Thanks to the perfect combustion of the propane gas, the combustion residues are minimum and the heating efficiency maximum: 100%.









BIG HEATING CAPACITY, EASY TO OPERATE


Easy to transport anywhere they are needed, the start-up is immediate, as is the maximum production of hot air. Moreover, the automatic models (GP/A) can be equipped with a thermostat, humidistat and timer which allow the regulation and control of the heat.

RELIABILITY

The project derives from long and consolidated experience in the sector, the materials are carefully selected and production is scrupulously controlled.

SAFETY

The GP/A models are equipped with an electronic devices for flame control, fuel feed and lighting the gas. The GP/M models have a safety thermocouple to cut off the fuel supply in the case of a flickering flame or should the flame go out as well as a piezo-electric system for lighting the gas.



- 1 COMBUSTION CHAMBER
- 2 BURNER
- 3 FAN
- 4 MOTOR
- PRESSURE REGULATOR
- 6 GAS CUT-OFF VALVE
- GAS LINI
- 8 LPG FLOW ELECTROMAGNETIC VALVE
- 9 LPG NOZZLE
- 10 CONTROL UNIT
- Automatic built in LPG burner
- Electronic control box (GP/A)
- Set to be connected to a thermostat or a timer (GP/A)
- Safety thermostat
- Ionization flame control (GP/A)
- Thermo-electric flame control (GP/M)
- · Power cord with plug
- Pressure reducer adjustable
- Gas pipe with connections
- Excess flow cut off valve
- Automatic ignition (GP/A)
- Piezoelectric ignition (GP/M)
- Summer-winter switch for use as fan

MODEL	HEATING POWER		HEATED AIR	TEMPERAT. RISE	CONSUMPTION AND FEEDING PRESSURE		POWER SUPPLY	ELECTRICAL POWER	DIMENSION (LxWxH)	NET WEIGHT
	kW	kcal/h	m³/h	°C	G30 kg/h-mbar	G31 kg/h-mbar	V, ∼, Hz	W	mm	kg
GP 25 M	13,9÷30,2	12.000÷26.000	650	64÷138	1,10/2,38-500/2.000	1,08/2,35-500/2.000	230, 1, 50	50	525x280x420	11,5
GP 45 M	19,8÷52,3	17.000÷45.000	1.400	42÷110	1,56/4,13-500/2.000	1,54/4,06-500/2.000	230, 1, 50	125	558x455x554	16
GP 60 M	30,2÷73,6	26.000÷63.300	2.100	43÷104	2,39/5,81-500/2.000	2,36/5,72-500/2.000	230, 1, 50	180	775x443x546	20
GP 90 M	32,6÷96,5	28.000÷83.000	3.260	29÷88	2,57/7,61-500/2.000	2,53/7,50-500/2.000	230, 1, 50	325	1.015x435x610	35
GP 25 A	13,9÷30,2	12.000÷26.000	650	64÷138	1,10/2,38-500/2.000	1,08/2,35-500/2.000	230, 1, 50	59	525x280x420	11,5
GP 45 A	19,8÷52,3	17.000÷45.000	1.400	42÷110	1,56/4,13-500/2.000	1,54/4,06-500/2.000	230, 1, 50	145	558x455x554	16
GP 60 A	30,2÷73,6	26.000÷63.300	2.100	43÷104	2,39/5,81-500/2.000	2,36/5,72-500/2.000	230, 1, 50	200	775x443x546	20
GP 90 A	32,6÷96,5	28.000÷83.000	3.260	29÷88	2,57/7,61-500/2.000	2,53/7,50-500/2.000	230, 1, 50	345	1.015x435x610	35

The technical specifications are not binding and we reserve the right to change them without notice



COMPANY
WITH QUALITY SYSTEM
CERTIFIED BY DNV
=ISO 9001/2000=

BIEMMEDUE SpA Via Industria, 12 - 12062 CHERASCO (CN) Tel. +39 0172 486111 - Fax +39 0172 488270 www.biemmedue.com - e-mail: bm2@biemmedue.com



Get In Touch

Call: <u>0845 6880112</u>

Email: <u>info@adremit.co.uk</u>

