


**Technical data sheet**



# AD-25-H-100-030



Evaporative cooler with side air outlet

|                 | DESCRIPTION                            | UNITS               | DATA                                 |
|-----------------|--|---------------------|--------------------------------------|
| AIR FLOW        | Air flow                               | m <sup>3</sup> /h   | 18.140                               |
|                 | Available static pressure              | Pa                  | 100                                  |
| ENGINE          | Rated power                            | kW                  | 3,00                                 |
|                 | Nominal consumption                    | A                   | 6,33 A (400V III) 11,50 A (230V III) |
|                 | Speeds                                 | Units               | 1 speed / frequency inverter         |
|                 | Tension                                | V/Phases/Hz         | 400/III/50 Hz                        |
|                 | Regulation type                        | -                   | 1 speed / frequency inverter         |
| FAN             | Typo                                   | -                   | Centrifuge                           |
|                 | Diameter                               | mm                  | -                                    |
|                 | Speed                                  | Rpm                 | 522 (PM-90 PV-250)                   |
|                 | Drive belts                            | Units               | 2 x XPA 1900                         |
| PUMP            | Model                                  | -                   | WILO TM 32/7                         |
|                 | Power / Nominal consumption            | -                   | 250W / 1,50 A                        |
|                 | Flow (2m height)                       | l/m                 | 115                                  |
|                 | Tension                                | V/Phases/Hz         | 230/I/50                             |
|                 | Level switch                           | -                   | Yes                                  |
| COOLING         | Panel type                             | -                   | 5090                                 |
|                 | Dimensions                             | mm                  | 1000x600x100                         |
|                 | Quantity                               | Units               | 6                                    |
|                 | Total panel surface                    | m <sup>2</sup>      | 3,60                                 |
|                 | Panel air speed                        | m/s                 | 1,39                                 |
|                 | Panel efficiency                       | %                   | 88                                   |
|                 | Temperature impulsion (40°C – 30% HR)  | °C                  | 26,9 °C                              |
|                 | Pre filter G4                          | -                   | Optional                             |
| SOUND LEVEL     | Sound level                            | dB (A) 3m           | 68                                   |
| CONNECTIONS     | Inlet solenoid valve                   | Inches              | ½"                                   |
|                 | Water evacuation                       | Inches              | 1 ¼"                                 |
|                 | Overflow                               | Inches              | 1"                                   |
| CLEANING SYSTEM | Automatic emptying                     | -                   | SI                                   |
|                 | UV lamp                                | -                   | Optional                             |
| CONTROL TYPE    | Electric panel 1 speed                 | -                   | Optional                             |
|                 | Electric panel with frequency inverter | -                   | Optional                             |
| DIMENSIONS      | Overall dimensions                     | Width/Length/Height | 1510x1551x1398mm                     |
|                 | Mouthpiece connexion dimensions        | Width/length        | 640x640mm                            |
|                 | Empty weight / operating               | Kg                  | 342 / 425                            |
| CERTIFICATES    |  |                     | CE                                   |

 METALURGICA MANLLEUENSE, S.A. | Tel. +34 93 851 15 99 | [www.metmann.com](http://www.metmann.com)  
 C/Fontcuberta, 32-36 | 08560-Manlleu (Barcelona) SPAIN

**Get In Touch**
 **Call:** 0845 6880112  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)
**Our Address**

 Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH




# AD-25-H-100-030

Evaporative cooler with side air outlet



## Prestaciones AD-25 (3 kW)



## Standard design details


- Water tray made of polyamide
- Corner and central posts in stainless steel AISI-304
- Top roof, side outlet and inlet grilles in galvanised polyester powder coated (INOX version in AISI-304)
- Cooling panels type 5090 of 100mm thick
- Centrifugal fan unit with forward blades and hot-dip galvanised frame
- Automatic draining system patented by MET MANN
- SCHAEFFLER CORROTECT corrosion-resistant bearings with protective caps
- Maintenance-free QUAD-POWER4 power transmission belts from GATES
- WILO IP 68 water pump with level switch
- High efficiency electric motor IE3 IP 55
- Normally closed inlet solenoid valve
- Half-turn opening system for access to the inside of the unit
- Base stand with legs supplied as standard for ease of transport and installation

## Custom manufacturing

- Air filtration to comply with BRC food standards
- Customized air flows and pressures
- ATEX motors for explosive environments, etc...

METALURGICA MANLLEUENSE, S.A. | Tel. +34 93 851 15 99 | [www.metmann.com](http://www.metmann.com)  
C/Fontcuberta, 32-36 | 08560-Manlleu (Barcelona) SPAIN

### Get In Touch

 Call: 0845 6880112  
 Email: [info@adremmit.co.uk](mailto:info@adremmit.co.uk)

### Our Address

Puravent, Adremmit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH




Technical data sheet

# AD-25-H-100-030

Evaporative cooler with side air outlet



## Overall dimensions



METALURGICA MANLLEUENSE, S.A. | Tel. +34 93 851 15 99 | [www.metmann.com](http://www.metmann.com)  
C/Fontcuberta, 32-36 | 08560-Manlleu (Barcelona) SPAIN

### Get In Touch

Call: 0845 6880112  
Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH






Technical data sheet

# AD-25-H-100-030

Evaporative cooler with side air outlet



## Wall installation with diffuser



| POSITION | DESCRIPTION                                 | UNITS | STANDARD      | INOX          |
|----------|---|-------|---------------|---------------|
| 01       | Evaporative cooler AD-25-H-100-030          | 1     | 15012541030S  | 15012541030I  |
| 02       | Electric panel 1 speed / frequency inverter | 1     | 0415CMS030400 | 0415CF030400  |
| 03       | Base stand support KBM-40                   | 1     | 03091501027   |               |
| 04       | Coupling (640x640/850x850)                  | 1     | 180564648585  |               |
| 05       | Flexible joint JE-850 (850x850)             | 1     | 1805AV8585    |               |
| 06       | Straight section TR-850 (850x850x1000)      | 1     | 1805TR850     |               |
| 07       | 3-way air diffuser DCH-3-40                 | 1     | 0323150140301 |               |
| -        | Pre filter PG4-25                           | 6     | 04150125G412  | 04150125G412I |
| -        | UV WATER treatment                          | 1     | 031501101010M |               |
| -        | Protective case FU-25-H                     | 1     | 03021502025H  |               |

METALURGICA MANLLEUENSE, S.A. | Tel. +34 93 851 15 99 | [www.metmann.com](http://www.metmann.com)  
 C/Fontcuberta, 32-36 | 08560-Manlleu (Barcelona) SPAIN

### Get In Touch

 Call: 0845 6880112  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH




Technical data sheet

# AD-25-H-100-030

Evaporative cooler with side air outlet



## Wall installation with impulsion nozzles



| POSITION | DESCRIPTION                                 | UNITS | STANDARD      | INOX          |
|----------|---|-------|---------------|---------------|
| 01       | Evaporative cooler AD-25-H-100-030          | 1     | 15012541030S  | 15012541030I  |
| 02       | Electric panel 1 speed / frequency inverter | 1     | 0415CMS030400 | 0415CF030400  |
| 03       | Base stand support KBM-40                   | 1     | 03091501027   |               |
| 04       | Coupling (640x640/850x850)                  | 1     | 180564648585  |               |
| 05       | Flexible joint JE-850 (850x850)             | 1     | 1805AV8585    |               |
| 06       | Straight section TR-850 (850x850x1000)      | 1     | 1805TR850     |               |
| 07       | High induction nozzles CI-300               | 1     | 04150PAKCONO  |               |
| -        | Pre filter PG4-25                           | 6     | 04150125G412  | 04150125G412I |
| -        | UV WATER treatment                          | 1     | 031501101010M |               |
| -        | Protective case FU-25-H                     | 1     | 03021502025H  |               |

METALURGICA MANLLEUENSE, S.A. | Tel. +34 93 851 15 99 | [www.metmann.com](http://www.metmann.com)  
 C/Fontcuberta, 32-36 | 08560-Manlleu (Barcelona) SPAIN

### Get In Touch

 Call: 0845 6880112  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH