



ADSORPTION DEHUMIDIFIERS INDUSTRIAL



DTM 3300



Features

- Weather proof
- Heavy duty outer frame
- Lifting eyes
- Stackable (3 high)
- Forklift guides
- Insulated housing in stainless steel
- PTC reactivation heater, eliminates the risk of overheating and allows step-less capacity control
- Touchscreen PLC controller, with humidity control via built in probe
- Rotation guard, filter alarm, run-time-meter, service alarm and fan run on timer as standard
- Fan speed control

Applications

- Temporary climate control
- Water damage
- Restoration drying
- Outdoor rental
- Dry air storage
- Military equipment
- Power stations and buildings



Specifications	Units	DTM 3300
Capacity (20°C/60% RH)	kg/h	14.7
Dry air flow (at 430 Pa available ext. pressure)	m ³ /h	3300
Wet air flow (at 300 Pa available ext. pressure)	m ³ /h	550
Sound level	dB(A)	70.4
Reactivation power	kW	18
Filter class		4
Product size (l x w x h)	mm	1309 x 1060 x 1266
Weight	kg	205

Get In Touch

 **Call:** 0845 6880112
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH

