



INDUSTRIAL DRYING

ADSORPTION



DT 13000



DT 27000



Features

- Insulated housing with panels and inspection doors
- Possible to transport by forklift
- Internal purge zone reducing energy consumption and increasing the capacity
- Control system



Applications

- Process air systems
- Store rooms
- Pharmaceutical production
- Pumping stations
- Film production
- Electronics manufacturing
- Confectionery and food production
- Museums and art galleries
- Cold storage



Specifications	Units	DT 13000	DT 19000	DT 27000
Dehumidification @ 20°C/60% RH	kg/h	86	126	182
Dry air flow	m³/h	13000	19000	27900
Available pressure	Pa	590	440	400
Wet air flow	m³/h	4200	6000	6980
Available pressure	Pa	200	450	250
Power consumption	kW	143.5	207.5	309.0
Power supply	V/Hz	400/3ph/50	400/3ph/50	400/3ph/50
Sound level	dB(A)	-	72	-
Reactivation power	kW	132	192	288
Electrical (E), steam (S), gas (G) react. option		E/S/G	E/S/G	E/S/G
Filter class		4	4	4
Product size (l x w x h)	mm	2250 x 1600 x 2300	2400 x 1900 x 2500	2900 x 1900 x 2500
Weight	kg	1350	1700	2400

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH