

INDUSTRIAL DRYING ADSORPTION



DT 160



DT 250

Optional accessories

- External humidistat connection
- Floor stand
- Wall bracket



Features

- Sturdy housing in stainless steel
- Low weight
- PTC reactivation heater, eliminates the risk for overheating and allows step-less capacity control
- The desiccant rotor, including its transmission element and fan, can be easily lifted out of the housing for external inspection and service

Applications



- Process air systems
- Store rooms
- Pharmaceutical production
- Pumping stations
- Film production
- Electronics manufacturing
- Confectionery and food production
- Museums and art galleries
- Cold storage

Specifications	Units	DT 160	DT 250	DT 440
Dehumidification @ 20°C/60% RH	kg/h	0.6	1.1	1.4
Dry air flow (free blowing)	m ³ /h	160	290	440
Available pressure	Pa	0	0	0
Wet air flow	m ³ /h	40	50	100
Available pressure	Pa	0	0	0
Power consumption	kW	1.0	1.3	2.1
Power supply	V/Hz	230/1ph/50	230/1ph/50	230/1ph/50
Sound level	dB(A)	53	52.9	69
Reactivation power	kW	0.8	1.2	1.9
Electrical (E), steam (S), gas (G) react. option		E	E	E
Filter class		3	3	3
Product size (l x w x h)	mm	324 x 329 x 274	335 x 351 x 357	335 x 351 x 357
Weight	kg	10.5	14	31

Get In Touch

- Call:** 0845 6880112
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH