

INDUSTRIAL DRYING ADSORPTION



DT 210



DT 400



Features

- Sturdy housing in stainless steel
- Low weight
- PTC reactivation heater, eliminates the risk for overheating and allows step-less capacity control
- The desiccant rotor, including its transmission element and fan, can be easily lifted out of the housing for external inspection and service

Optional accessories

- External humidistat connection
- Air cooled condenser (DT 210/450 only)
- Floor stand
- Wall bracket

Applications



- Process air systems
- Store rooms
- Pharmaceutical production
- Pumping stations
- Film production
- Electronics manufacturing
- Confectionery and food production
- Museums and art galleries
- Cold storage

Specifications	Units	DT 210	DT 400	DT 450
Dehumidification @ 20°C/60% RH	kg/h	0.6	1.5	2.2
Dry air flow	m ³ /h	210	400	450
Available pressure	Pa	0	30	0
Wet air flow	m ³ /h	40	120	120
Available pressure	Pa	0	0	0
Power consumption	kW	1.1	2.3	3.5
Power supply	V/Hz	230/1ph/50	230/1ph/50	230/1ph/50
Sound level	dB(A)	53.3	62.2	63
Reactivation power	kW	0.8	2.0	3.2
Electrical (E), steam (S), gas (G) react. option		E	E	E
Filter class		3	3	3
Product size (l x w x h)	mm	315 x 315 x 457	504 x 428 x 525.5	504 x 428 x 525.5
Weight	kg	16.5	28	31

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH