



INDUSTRIAL DRYING

ADSORPTION



DT 6000



DT 8000



Features

- Insulated housing with panels and inspection doors
- Possible to transport by forklift
- Internal purge zone reducing energy consumption and increasing the capacity
- Control system



Applications

- Process air systems
- Store rooms
- Pharmaceutical production
- Pumping stations
- Film production
- Electronics manufacturing
- Confectionery and food production
- Museums and art galleries
- Cold storage



Specifications	Units	DT 6000	DT 8000
Dehumidification @ 20°C/60% RH	kg/h	39	53
Dry air flow	m³/h	6000	8000
Available pressure	Pa	440	280
Wet air flow	m³/h	1700	2500
Available pressure	Pa	325	150
Power consumption	kW	54.2	79.5
Power supply	V/Hz	400/3ph/50	400/3ph/50
Sound level	dB(A)	73	73
Reactivation power	kW	48	72
Electrical (E), steam (S), gas (G) react. option		E/S/G	E/S/G
Filter class		4	4
Product size (l x w x h)	mm	2000 x 1350 x 1780	2000 x 1350 x 1780
Weight	kg	900	950

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH