

DEHUMIDIFIERS

WALL MOUNTED



CDF 10



CDF 10
with water tank

Optional accessories

- Room hygrostat
- Water tank, grey or white



Features



- Built into a strong and robust powder coated hot galvanized sheet metal cabinet
- Evaporator and condenser coils are epoxy-coated for high corrosion resistance
- The condensate outlet is located at the bottom of the CDF dehumidifier. The outlet stub can be connected to a water hose.
- Easy accessible washable air filters from front cover
- Reciprocating compressor
- Axial fan
- Electronic control and user-friendly display panel
- Active, demand-controlled defrosting
- Available in white and grey

Applications

- Archives and museums
- Churches
- Changing rooms
- Waterworks
- Garages and car storage

Specifications	Units	CDF 10
Operating temperature range	°C	3-30
Operating humidity range	% RH	40-100
Dehumidification @ 30°C/60% RH	l/24h	7.5
Air flow	m ³ /h	220
Power supply	V/Hz	230/1ph/50
Max. power consumption	kW	0.3
Sound pressure level @ 1m	dB(A)	46
Refrigerant		R134a
Water container capacity	l	5.5
Product size (h x w x d)	mm	600 x 535 x 240
Weight	kg	28

Get In Touch

-  **Call:** 0845 6880112
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH