

HIGH CAPACITY DEHUMIDIFIERS

DUCTED



GEMINI 2.1
GEMINI 2.2
GEMINI 2.3



Features

- Case made of galvanized steel
- Heat pump with heat recovery
- Condensate drain
- Two EC fans with high external pressure
- Four channel inlet ABL/ZUL'AMAN and FOL/AUL
- Three air flaps with servo motors
- Three sensors for the measurement of humidity, temperature and air pressure
- Bag filters

Applications

- Basements and cellars
- Underground rooms



Specifications	Units	Gemini 2.1	Gemini 2.2	Gemini 2.3
Operating temperature range	°C	5-30	5-30	5-30
Operating humidity range	%	40-95	40-95	40-95
Capacity (20°C/60% RH)	l/24h	25	45	97
Air flow	m³/h	300	450	800
Sound level @ 1m	dB(A)	26	26	26
Max. external pressure	Pa	250	250	250
Power consumption	kW	0.875	1.545	2.75
Power supply	V/Hz	230/1ph/50	230/1ph/50	230/1ph/50
Fuse	A	10	13	16
Product size (h x w x d)	mm	1275 x 1550 x 645	1275 x 1550 x 645	1410 x 1700 x 645
Weight	kg	400	410	430

Get In Touch

Call: [0845 6880112](tel:08456880112)
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH