



HIGH CAPACITY DEHUMIDIFIERS

DUCTED



CDP 75
CDP 125
CDP 165

Optional accessories

- Room hygostat
- Duct hygostat
- Room thermostat
- Water heating coil
- Shock-absorbing floor mounting kit
- Wall mounting kit
- Defrost sensor
- Failure monitoring kit

Applications

- Changing rooms
- Hotel pools
- Private pools
- Production areas
- Therapy pools
- Warehouses
- Wellness centres



Features

- The CDP 75-125-165 are built into a cabinet made of hot-galvanized, powder painted and double-skinned panels with 50mm insulation
- Evaporator and condenser coils are protected against corrosion
- The condensate outlet is located on the air inlet side
- The outlet stub can be connected to a water hose
- Air inlet through a filter placed in a removable frame
- Dry air outlet positioned either horizontally or vertically through the top of the unit
- The access for inspection can be moved to the opposite side
- Fresh air inlet possible through fresh air duct
- Can be supplied with an optional water-cooled condenser. Coupling pipes are made of copper
- Rotary/reciprocating compressor
- Radial fan
- CDP 75 and CDP 125 can be wall mounted using a wall mount kit
- CDP 75, CDP 125 and CDP 165 can be placed on the floor using a shock-absorbing floor mount kit (accessory)
- A water heating coil can be mounted in the air outlet duct for further heating of the dry air (accessory)

Specifications	Units	CDP 75	CDP 125	CDP 165
Dehumidification @ 28°C/60% RH	l/24h	74	124	162
Operating temperature range	°C	20-38	20-38	20-38
Operating humidity range	%	40-100	40-100	40-100
Air flow	m³/h	1500	2500	3600
Power supply	V/Hz	230/1ph/50	230/1ph/50 + 400/3ph/50	400/3ph/50
Sound level	dB(A)	58	60	63
Product size (h x w x d)	mm	650 x 1155 x 725	850 x 1300 x 900	975 x 1400 x 1010
Weight	kg	130	160	190
Water-cooled condenser		Optional	Optional	Optional

TO DRY

Get In Touch

Call: 0845 6880112
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

