



PA2510E05 AIR CURTAIN

Item no. 8662

Document type: **Product card**
 Document date: **2019-07-03**
 Generated by: **Systemair Online Catalogue**

Description

Stylish air curtain for entrances, with intelligent control

- Recommended installation height 2,5 m
- Horizontal mounting

Application

The PA2500 creates a temperature dividing air barrier that effectively prevents cold drafts and gives excellent heating comfort in door ways, such as shops, offices and public offices.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

Design

The PA2500 has a modern and stylish design developed to fit all entrances. A recess on the upper side of the unit with electrical heating simplifies installation and makes it more attractive. A recess on the upper side of the unit with electrical heating simplifies installation and makes it more attractive. The front can be finished in any colour to perfectly match the environment.



Technical parameters

Unit	
Type of installation	Horizontal
Type of heating	Electrical heat
Length	1050 mm
Height	209 mm
Depth	345 mm
Weight	19 kg
Max. installation height	2500 mm
Color casing	RAL 9016, NCS S 0500-N
Color, outlet grilles	RAL 7046
Protection class	IP20
Ambient working temperature range (dry conditions)	-20-30 °C
Air flow	
Air flow step 3	1450 m³/h
Air flow step 2	1150 m³/h
Air flow step 1	900 m³/h
Sound data	
Sound power level LWA	68 dB(A)
Sound level step 3	51 dB(A)
Sound level step 2	47 dB(A)
Sound level step 1	42 dB(A)

Get In Touch

Call: [0845 6880112](tel:08456880112)
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH






Control/motor data		
Control/motor supply	230	V
Control/motor current	0,5	A
Max fan rpm	1250	r.p.m.
Motor power	0,12	kW
Heater		
Supply voltage heating	400	V
Phase	3	~
Electric heating 100%	5	kW
Electric heating 66%	3,3	kW
Electric heating 33%	1,7	kW
Current heating 100%	7,2	A
Current heating 66%	4,8	A
Current heating 33%	2,5	A
Temperature rise, maximum heat output, highest airflow	10,5	°C
Temperature rise, maximum heat output, lowest airflow	17	°C

Accessories

Accessories

- [SIRETX Room sensor \(17539\)](#)
- [SIRECC603 3m Modular cable \(17542\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC610 10m Modular cable \(17544\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [SIRECC403 3m Modular cable \(17546\)](#)
- [SIRECC405 5m Modular cable \(17547\)](#)
- [SIRECC410 10m Modular cable \(17548\)](#)
- [SIRECC415 15m Modular cable \(17549\)](#)
- [PA34TR15 Threaded rods \(18056\)](#)
- [PAMLK \(18690\)](#)
- [PA2PF15 Pendulum brackets \(19415\)](#)
- [PA2P15 Pendulum bar \(19568\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

Documentation

-  [ma_frico_pa2500_gb_170619.pdf \(1,33MB\)](#)
-  [ma_frico_pa2p_pa2pf_pa34tr_160114.pdf \(501,76kB\)](#)
-  [ma_frico_pamlk_low.pdf \(549,72kB\)](#)
-  [cat_frico_pa2500_gb_20170612.pdf \(417,45kB\)](#)
-  [cat_frico_ac_sire_valves_gb_20170523.pdf \(345,98kB\)](#)
-  [Wiring diagram PA2500.pdf \(96,44kB\)](#)

Name: **PA2510E05 AIR CURTAIN** | Item no.: **8662**




Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

Get In Touch

-  **Call:** [0845 6880112](tel:08456880112)
-  **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

 DoC Air curtains_gb 2017-04.pdf (224,51kB) PA2510E05-3D.dxf (87,05kB) PA2510E-2D.dwg (1,77MB)

Specification text

Stylish air curtain for entrances, with intelligent control

- Recommended installation height 2,5 m*
- Horizontal mounting

Application

The PA2500 creates a temperature dividing air barrier that effectively prevents cold drafts and gives excellent heating comfort in door ways, such as shops, offices and public offices.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

Design

The PA2500 has a modern and stylish design developed to fit all entrances. A recess on the upper side of the unit with electrical heating simplifies installation and makes it more attractive. A recess on the upper side of the unit with electrical heating simplifies installation and makes it more attractive. The front can be finished in any colour to perfectly match the environment.

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH