



# PA3215CE12 AIR CURTAIN

Item no. 19804

Document type: **Product card**  
 Document date: **2019-07-03**  
 Generated by: **Systemair Online Catalogue**

## Description

### Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m
- Horizontal mounting

#### Application

PA3200C is a compact air curtain for commercial building entrances. The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

PA3200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

#### Design

With its timeless design PA3200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.



## Technical parameters

Unit	
Type of installation	Horizontal
Type of heating	Electrical heat
Length	1578 mm
Height	256 mm
Depth	458 mm
Weight	30 kg
Max. installation height	3200 mm
Color casing	RAL 9016, NCS S 0500-N
Color, outlet grilles	RAL 7046
Protection class	IP20
Ambient working temperature range (dry conditions)	-20-30 °C
Air flow	
Air flow step 3	2750 m³/h
Air flow step 2	2200 m³/h
Air flow step 1	1700 m³/h
Sound data	
Sound power level LWA	75 dB(A)
Sound level step 3	59 dB(A)
Sound level step 2	52 dB(A)
Sound level step 1	46 dB(A)

### Get In Touch

Call: [0845 6880112](tel:08456880112)  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





Control/motor data		
Control/motor supply	230	V
Control/motor current	1	A
Motor power	0,23	kW
Heater		
Supply voltage heating	400	V
Phase	3	~
Electric heating 100%	12	kW
Electric heating 50%	8	kW
Current heating 100%	17,3	A
Current heating 50%	11,5	A
Temperature rise, maximum heat output, highest airflow	13	°C
Temperature rise, maximum heat output, lowest airflow	21	°C

## Accessories

### Accessories

[PA34TR15 Threaded rods \(18056\)](#)

[PAMLK \(18690\)](#)

[PA2P15 Pendulum bar \(19568\)](#)

[PA2DR Remote + door contact \(15662\)](#)

[PA3PF15 Pendulum brackets \(25256\)](#)

## Documentation



[ma\\_frico\\_pa3200c\\_gb\\_170619.pdf \(2,06MB\)](#)



[ma\\_frico\\_pa2p\\_pa2pf\\_pa34tr\\_160114.pdf \(501,76kB\)](#)



[ma\\_frico\\_pa2dr.pdf \(157,01kB\)](#)



[ma\\_frico\\_pamlk\\_low.pdf \(549,72kB\)](#)



[cat\\_frico\\_pa3200c\\_gb\\_20170612.pdf \(482,94kB\)](#)



[DoC Air curtains\\_gb 2017-04.pdf \(224,51kB\)](#)



[Bpd Air curtain PA-PL32xxCE.pdf \(178,08kB\)](#)



[PA3215CE12-3D.dxf \(92,05kB\)](#)



[PA3215CE-2D.dwg \(422,23kB\)](#)

## Specification text

### Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m
- Horizontal mounting

#### Application

PA3200C is a compact air curtain for commercial building entrances. The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

PA3200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

#### Design

With its timeless design PA3200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.

Name: **PA3215CE12 AIR CURTAIN** | Item no.: **19804**

Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

2 / 2

## Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

## Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH