



PA3215CW AIR CURTAIN

Item no. 19810

Document type: Product card Document date: 2019-07-03

Generated by: Systemair Online Catalogue

Description

Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m
- · Horizontal mounting

Application

PA3200C is a compact air curtain for commercial building entrances. The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

PA3200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

Design

With its timeless design PA3200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.



Technical parameters

Unit		
Type of installation	Horizontal	
Type of heating	Water heat	
Length	1578	mm
Height	256	mm
Depth	458	mm
Weight	30	kg
Max. installation height	3200	mm
Color casing	RAL 9016, NCS S 0500- N	
Color, outlet grilles	RAL 7046	
Protection class	IP20	
Ambient working temperature range (dry conditions)	-20-30	°C
Air flow		
Air flow step 3	2700	m³/h
Air flow step 2	2250	m³/h
Air flow step 1	1850	m³/h
Sound data		
Sound power level LWA	73	dB(A)
Sound level step 3	57	dB(A)
Sound level step 2	52	dB(A)
Sound level step 1	46	dB(A)

Name: PA3215CW AIR CURTAIN | Item no.: 19810

Document type: Product card | Document date: 2019-07-03 | Generated by: Online catalogue



Get In Touch

Call: <u>0845 6880112</u>



Email: info@adremit.co.uk

1/3



Control/motor data		
Control/motor supply	230	V
Control/motor current	0,7	А
Motor power	0,16	KW
Heater		
Max. water temperature	110	°C
Max. working pressure	16	bar
Dimension water connections	DN20 (3/4")	
Water content in coil	0,7	I
Water heating full output 60/40 °C, air +18 °C	13,9	KVV
Pressure drop water 60/40 °C, air +18 °C	6,3	kPa

Accessories

Accessories

VOT15 valve kit (19031)

VOT20 valve kit (19032)

VOT25 valve kit (19033)

PA34TR15 Threaded rods (18056)

PAMLK (18690)

PA3EF10 Ext. inlet filt PIII (18746)

PA3EF15 Ext. inlet filt PIII (18747)

PA2P15 Pendulum bar (19568)

PA2DR Remote + door contact (15662)

PA3PF15 Pendulum brackets (25256)

SD230 Actuator 230V (16979)

VLSP15LF Valve system (79379)

VLSP15NF Valve system (79380)

VLSP20 Valve system (79381) VLSP25 Valve system (79382)

VLSP32 Valve system (79417)

Documentation

ma_frico_pa3200c_gb_170619.pdf (2,06MB)

ma_frico_pa2p_pa2pf_pa34tr_160114.pdf (501,76kB)

ma_frico_pa2dr.pdf (157,01kB)

ma_frico_pamlk_low.pdf (549,72kB)

at_frico_pa3200c_gb_20170612.pdf (482,94kB)

DoC Air curtains_gb 2017-04.pdf (224,51kB)

Bpd Air curtain PA-PL32xxCW.pdf (179,63kB)

PA3215CW-3D.dxf (130,14kB) PA3215CW-2D.dwg (425,06kB)

Name: PA3215CW AIR CURTAIN | Item no.: 19810

Document type: Product card | Document date: 2019-07-03 | Generated by: Online catalogue









Specification text

Stylish air curtain for commercial premises, with remote and integrated control

- Recommended installation height 3,2 m
- · Horizontal mounting

Application

PA3200C is a compact air curtain for commercial building entrances. The air curtain has an integrated control system and can also be remote controlled which makes it very easy to install and use.

PA3200C creates a temperature dividing air barrier that effectively prevents cold draughts and gives excellent heating comfort inside the door.

Desigr

With its timeless design PA3200C is suitable for all entrances. The air curtain has a control panel discretely integrated in the end, which makes cable routing unnecessary. The front can be finished in any colour to perfectly match the environment.

Name: PA3215CW AIR CURTAIN | Item no.: 19810

Document type: Product card | Document date: 2019-07-03 | Generated by: Online catalogue



Get In Touch

Call: 0845 6880112

Email: info@adremit.co.uk