



# PA3520WLL AIR CURTAIN

Item no. 16965

Document type: **Product card**  
 Document date: **2019-07-03**  
 Generated by: **Systemair Online Catalogue**

## Description

### Stylish air curtain for commercial premises, with intelligent control

- Horizontal mounting
- Installation height up to 3,5 metres\*
- Vertical mounting
- Installation width up to 5 metres\*  
(2 units), one on each side

### Application

Air curtain PA3500 gives more possibilities than ever before, packed into the same product. There are therefore many areas of use. PA3500 is particularly suitable for entrances to stores and shopping centres for example. The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

### Design

Through its timeless design and its many accessories, it's easy to get PA3500 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.

## Technical parameters

Unit	
Type of installation	Horizontal/Vertical
Type of heating	Water heat
Length	2039 mm
Height	306 mm
Depth	525 mm
Weight	78 kg
Max. installation height	3500 mm
Color casing	RAL 9016, NCS S 0500-N
Color, outlet grilles	RAL 7046
Protection class	IP21
Ambient working temperature range (dry conditions)	-20-30 °C
Air flow	
Air flow step 5	3700 m³/h
Air flow step 4	3300 m³/h
Air flow step 3	2700 m³/h
Air flow step 2	2200 m³/h
Air flow step 1	1700 m³/h

### Get In Touch

Call: [0845 6880112](tel:08456880112)  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH







Sound data		
Sound power level LWA	77	dB(A)
Sound level step 5	62	dB(A)
Sound level step 4	60	dB(A)
Sound level step 3	56	dB(A)
Sound level step 2	51	dB(A)
Sound level step 1	45	dB(A)
Control/motor data		
Control/motor supply	230	V
Phase	1	~
Control/motor current, 50Hz	4	A
Control/motor current, 60Hz	5,5	A
Motor power 50Hz	920	W
Motor power 60Hz	1270	W
Heater		
Max. water temperature	110	°C
Max. working pressure	16	bar
Dimension water connections	DN20	
Water content in coil	5,6	l
Water heating full output 40/30 °C, air +18 °C	16,1	kW
Pressure drop water 40/30 °C, air +18 °C	8,3	kPa

**Accessories**

**Electric accessories**

- [SIREDC Door contact \(17495\)](#)
- [SIRERTX Room sensor \(17539\)](#)
- [SIRECC603 3m Modular cable \(17542\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC610 10m Modular cable \(17544\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [SIRECC640 40m RJ12 on. cable \(17773\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

**Get In Touch**

 **Call:** 0845 6880112  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)

**Our Address**












Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH



## Accessories

[SIREWTA Sensor \(17613\)](#)  
[VOSP15LF valve kit \(17522\)](#)  
[VOSP15NF valve kit \(17523\)](#)  
[PA34EF20 External inlet filter \(19066\)](#)  
[PA3XT20 Outlet extension \(19087\)](#)  
[PA3DW20 Design kit wall \(110836\)](#)  
[PA34CB20 Ceiling brackets \(18060\)](#)  
[PA3JK Vertical kit/Joining kit \(110759\)](#)  
[PA34WB20 Wall brackets \(18045\)](#)  
[PA34WS20 Wire suspension \(18063\)](#)  
[PA34VD20 Vibration damper \(18066\)](#)  
[PA34TR20 Threaded rods \(18057\)](#)  
[PA3VDW20 Design kit vertical \(110752\)](#)  
[SD230 Actuator 230V \(16979\)](#)  
[ST23024 Transformer for 24V \(16981\)](#)  
[DTV200S Filterguard 20-300 Pa \(17597\)](#)  
[VLP15LF Valve system \(79375\)](#)  
[VLP15NF Valve system \(79376\)](#)  
[VLP20 Valve system \(79377\)](#)  
[VLP25 Valve system \(79378\)](#)  
[VLSP15LF Valve system \(79379\)](#)  
[VLSP15NF Valve system \(79380\)](#)  
[VLSP20 Valve system \(79381\)](#)  
[VLSP25 Valve system \(79382\)](#)  
[VLP32 Valve system \(79416\)](#)  
[VLSP32 Valve system \(79417\)](#)  
[SDM24 Actuator 24V \(16977\)](#)

## Documentation

-  [ma\\_frico\\_pa3500-4200\\_gb\\_180926.pdf \(3,49MB\)](#)
-  [ma\\_frico\\_PA3JK\\_PA4JK\\_PA34VDW\\_vertical.pdf \(1,53MB\)](#)
-  [ma\\_frico\\_PA3XT\\_PA4XT\\_150415.pdf \(381,55kB\)](#)
-  [ma\\_frico\\_pa34tr\\_pa34cb-pa34vd.pdf \(739,11kB\)](#)
-  [ma\\_frico\\_pa34ws\\_pa34cb.pdf \(916,13kB\)](#)
-  [ma\\_pa34jk\\_pa34dw\\_horizontal.pdf \(1,74MB\)](#)
-  [cat\\_frico\\_pa3500\\_pa4200\\_gb.pdf \(1,43MB\)](#)
-  [cat\\_frico\\_ac\\_sire\\_valves\\_gb\\_20170523.pdf \(345,98kB\)](#)
-  [wd\\_frico\\_pa3500\\_gb.pdf \(168,30kB\)](#)
-  [DoC Air curtains\\_gb 2017-04.pdf \(224,51kB\)](#)
-  [pa3520w-3D\\_1.dwg \(376,72kB\)](#)
-  [pa3520w-2D\\_1.dwg \(208,58kB\)](#)

Name: **PA3520WLL AIR CURTAIN** | Item no.: **16965**

Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

3 / 4

### Get In Touch

 **Call:** [0845 6880112](tel:08456880112)  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH



## Specification text

### Stylish air curtain for commercial premises, with intelligent control

- Horizontal mounting
    - Installation height up to 3,5 metres\*
  - Vertical mounting
    - Installation width up to 5 metres\*
- (2 units), one on each side

#### Application

Air curtain PA3500 gives more possibilities than ever before, packed into the same product. There are therefore many areas of use. PA3500 is particularly suitable for entrances to stores and shopping centres for example.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

#### Design

Through its timeless design and its many accessories, it's easy to get PA3500 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.

#### Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

#### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH