



PA3525A AIR CURTAIN

Item no. 9923

Document type: **Product card**

Document date: **2019-07-03**

Generated by: **Systemair Online Catalogue**

Description

Stylish air curtain for commercial premises, with intelligent control

- Horizontal mounting
- Installation height up to 3,5 metres*
- Vertical mounting
- Installation width up to 5 metres*
(2 units), one on each side

Application

Air curtain PA3500 gives more possibilities than ever before, packed into the same product. There are therefore many areas of use. PA3500 is particularly suitable for entrances to stores and shopping centres for example.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

Design

Through its timeless design and its many accessories, it's easy to get PA3500 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

*) Recommended installation height and width varies depending on the relevant premises.

Accessories

Accessories

- [SIRERTX Room sensor \(17539\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [PA34EF25 External inlet filter \(19067\)](#)
- [PA3XT25 Outlet extension \(19088\)](#)
- [PA34VD30 Vibration damper \(18067\)](#)
- [PA3DW25 Design kit wall \(110837\)](#)
- [PA3JK Vertical kit/Joining kit \(110759\)](#)
- [PA34WB30 Wall brackets \(18046\)](#)
- [PA34WS30 Wire suspension \(18064\)](#)
- [PA3VDW25 Design kit vertical \(110753\)](#)
- [PA34TR30 Threaded Rods \(18058\)](#)
- [PA34CB30 Ceiling Bracket \(18061\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

Technical parameters

Unit		
Type of installation	Horizontal/Vertical	
Type of heating	No heat	
Length	2549	mm
Height	270	mm
Depth	525	mm
Weight	79	kg
Max. installation height	3500	mm
Color casing	RAL 9016, NCS S 0500-N	
Color, outlet grilles	RAL 7046	
Protection class	IP21	
Ambient working temperature range (dry conditions)	-20-30 °C	
Air flow		
Air flow step 5	5250	m³/h
Air flow step 4	4500	m³/h
Air flow step 3	3600	m³/h
Air flow step 2	2850	m³/h
Air flow step 1	2400	m³/h
Sound data		
Sound power level LWA	80	dB(A)
Sound level step 5	64	dB(A)
Sound level step 4	60	dB(A)
Sound level step 3	55	dB(A)
Sound level step 2	50	dB(A)
Sound level step 1	44	dB(A)
Control/motor data		
Control/motor supply	230	V
Phase	1	~
Control/motor current, 50Hz	6,5	A
Control/motor current, 60Hz	7,3	A
Motor power 50Hz	1500	W
Motor power 60Hz	1600	W


Get In Touch


 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk


Our Address


Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

Documentation

-  ma_frico_pa3500-4200_gb_180926.pdf (3,49MB)
-  ma_frico_PA3JK_PA4JK_PA34VDW_vertical.pdf (1,53MB)
-  ma_frico_PA3XT_PA4XT_150415.pdf (381,55kB)
-  ma_frico_pa34tr_pa34cb-pa34vd.pdf (739,11kB)
-  ma_frico_pa34ws_pa34cb.pdf (916,13kB)
-  ma_pa34jk_pa34dw_horizontal.pdf (1,74MB)

-  cat_frico_pa3500_pa4200_gb.pdf (1,43MB)
-  cat_frico_ac_sire_valves_gb_20170523.pdf (345,98kB)

-  wd_frico_pa3500_gb.pdf (168,30kB)

-  DoC Air curtains_gb 2017-04.pdf (224,51kB)

-  PA3525A-3D.dxf (96,48kB)
-  pa3525e20-2D_1.dwg (211,03kB)

Name: **PA3525A AIR CURTAIN** | Item no.: **9923**

Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

3 / 4

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

Specification text

Thermozone Air Curtain - PA3500A & PA4200A

Innovative new generation type of air curtains, designed for either horizontal or vertical mounting with air circulation in neutral, compact design with integrated and intelligent control system SIRE

Housing

The self-supporting compact unit construction is made of galvanized sheet steel. The housing and galvanized sheet metal are Zink plated (Z275) with a thickness of 35 um. Visible surfaces with high-quality plastic powder coated (polyester powder coating, 60 um) in a subtle gray and white combination of both RAL9016 and RAL7046. A dominant and timeless design, hinged front and front access panel, high-grade aluminum allows integrating technical detail for each input. With M8 nuts, the air curtain is simple and easy to mount on the wall or ceiling. Matching design panels for cable connections are available as accessories for every type of installation. For vertical installations of either single or several air curtains, vertical installation accessories are available for each specific needs and requirement.

Fans

Vibration-free individually driven, double inlet five -stage variable high performance centrifugal fans with external rotor motor for extremely quiet operation, IP 44, with accessible motor protection and thermal contacts with class F insulation and ensure low noise operation. The newly developed sound-absorbing lined air outlet pressure chamber provides the internal air flow for reduced emissions of the engine noise and the formation of a highly effective flow profile.

Inlet grille

Integrated and located on top of the unit, not visible from below for hiding dust; guarantees a quiet slipstream.

Outlet grille

The streamlined grey powder coated outlet nozzle rod profiles, are lockable between 0 ° and 30 ° (in and out) and creates and provides a guided, aerodynamic air flow and high shielding effectiveness; Thermozone Technology.

Electrical connection

The main control connection is mounted and located on the top of the device and easily accessible to its integrated control system and designed according to ISO 9001:2000.

Control system

The provided control system should be an intelligent and adaptive control system, allowing and operating the installed air curtain with five different fan speed for being energy efficient as possible yet providing the best and most efficient air curtain effect. Including the control system, a calendar program can easily be set and adjusted according to each specific needs for the air curtain of operating without any manual handling. The air curtain can together with included and installed control system be also connected to either 0-10V or Modbus BMS system.

Certification

The air curtain must comply to EN and ISO standards valid for air curtains and tested and approved according ISO standards (ISO 27327-1), EN standards (EN 308; EN 12238; EN 60335) and AMCA standards (AMCA 210; AMCA 220-5; AMCA 300).

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH