



# PA4220WH IPX4 AIR CURTAIN

Item no. 26401

Document type: **Product card**  
 Document date: **2019-07-03**  
 Generated by: **Systemair Online Catalogue**

## Description

### Stylish air curtain for commercial and industrial premises, with intelligent control

- Horizontal mounting
- Recommended installation height 4,2 m\*
- Vertical mounting
- Recommended installation width 6 m\*  
(2 units), one on each side

### Application

With air curtain PA4200 there are more opportunities than ever before, packed into the same product. There are therefore many areas of use. PA4200 is specifically designed for doorways in for example, large commercial installations or industrial and warehouse buildings. The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

### Design

Through its timeless design and its many accessories, it's easy to get PA4200 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.

## Technical parameters

| Unit   |                        |
|--|------------------------|
| Type of installation                               | Horizontal/Vertical    |
| Type of heating                                    | Water heat             |
| Length   | 2039 mm                |
| Height   | 331 mm                 |
| Depth  | 611 mm                 |
| Weight   | 87 kg                  |
| Max. installation height                           | 4200 mm                |
| Color casing                                       | RAL 9016, NCS S 0500-N |
| Color, outlet grilles                              | RAL 7046               |
| Protection class                                   | IPX4                   |
| Ambient working temperature range (dry conditions) | -20-30 °C              |
| Air flow   |                        |
| Air flow step 5                                    | 5300 m³/h              |
| Air flow step 4                                    | 4600 m³/h              |
| Air flow step 3                                    | 3500 m³/h              |
| Air flow step 2                                    | 2700 m³/h              |
| Air flow step 1                                    | 2200 m³/h              |

### Get In Touch

Call: [0845 6880112](tel:08456880112)  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH





| Sound data                                     |      |        |
|--|------|--------|
| Sound power level LWA                          | 82   | dB(A)  |
| Sound level step 5                             | 66   | dB(A)  |
| Sound level step 4                             | 63   | dB(A)  |
| Sound level step 3                             | 56   | dB(A)  |
| Sound level step 2                             | 51   | dB(A)  |
| Sound level step 1                             | 46   | dB(A)  |
| Control/motor data                             |      |        |
| Control/motor supply                           | 230  | V      |
| Phase  | 1    | ~      |
| Control/motor current, 50Hz                    | 8,4  | A      |
| Max fan rpm                                    | 2050 | r.p.m. |
| Motor power 50Hz                               | 1930 | W      |
| Heater   |      |        |
| Max. water temperature                         | 110  | °C     |
| Max. working pressure                          | 16   | bar    |
| Dimension water connections                    | DN20 |        |
| Water content in coil                          | 2,7  | l      |
| Water heating full output 80/60 °C, air +18 °C | 30   | kW     |
| Pressure drop water 80/60 °C, air +18 °C       | 18   | kPa    |

## Accessories

### Electric accessories

- [SIREDC Door contact \(17495\)](#)
- [SIRERTX Room sensor \(17539\)](#)
- [SIRECC603 3m Modular cable \(17542\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC610 10m Modular cable \(17544\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [SIRECC640 40m RJ12 on. cable \(17773\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

### Get In Touch

 **Call:** [0845 6880112](tel:08456880112)  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)













### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH

## Accessories

[SIREWTA Sensor \(17613\)](#)  
[PA34EF20 External inlet filter \(19066\)](#)  
[PA4XT20 Outlet extension \(19092\)](#)  
[PA4DW20 Design kit wall \(110840\)](#)  
[PA34CB20 Ceiling brackets \(18060\)](#)  
[PA4JK Vertical kit/Joining kit \(110760\)](#)  
[PA34WB20 Wall brackets \(18045\)](#)  
[PA34WS20 Wire suspension \(18063\)](#)  
[PA34VD20 Vibration damper \(18066\)](#)  
[PA34TR20 Threaded rods \(18057\)](#)  
[PA4VDW20 Design kit vertical \(110755\)](#)  
[SD230 Actuator 230V \(16979\)](#)  
[ST23024 Transformer for 24V \(16981\)](#)  
[DTV200S Filterquard 20-300 Pa \(17597\)](#)  
[VLP15LF Valve system \(79375\)](#)  
[VLP15NF Valve system \(79376\)](#)  
[VLP20 Valve system \(79377\)](#)  
[VLP25 Valve system \(79378\)](#)  
[VLSP15LF Valve system \(79379\)](#)  
[VLSP15NF Valve system \(79380\)](#)  
[VLSP20 Valve system \(79381\)](#)  
[VLSP25 Valve system \(79382\)](#)  
[VLP32 Valve system \(79416\)](#)  
[VLSP32 Valve system \(79417\)](#)  
[SDM24 Actuator 24V \(16977\)](#)

## Documentation

-  [ma\\_frico\\_pa3500-4200\\_gb\\_180926.pdf \(3,49MB\)](#)
-  [ma\\_frico\\_PA3JK\\_PA4JK\\_PA34VDW\\_vertical.pdf \(1,53MB\)](#)
-  [ma\\_frico\\_PA3XT\\_PA4XT\\_150415.pdf \(381,55kB\)](#)
-  [ma\\_frico\\_pa34tr\\_pa34cb-pa34vd.pdf \(739,11kB\)](#)
-  [ma\\_frico\\_pa34ws\\_pa34cb.pdf \(916,13kB\)](#)
-  [ma\\_pa34jk\\_pa34dw\\_horizontal.pdf \(1,74MB\)](#)
-  [cat\\_frico\\_ac\\_sire\\_valves\\_gb\\_20170523.pdf \(345,98kB\)](#)
-  [cat\\_frico\\_pa3500\\_pa4200\\_gb.pdf \(1,43MB\)](#)
-  [wd\\_frico\\_pa4200\\_gb.pdf \(168,25kB\)](#)
-  [DoC Air curtains\\_gb 2017-04.pdf \(224,51kB\)](#)
-  [Cad drawings \(dwg\) PA4220W 3D.dwg.dwg \(648,98kB\)](#)
-  [Cad drawings \(dwg\) PA4220W 2D.dwg.dwg \(166,74kB\)](#)

Name: **PA4220WH IPX4 AIR CURTAIN** | Item no.: **26401**

Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

3 / 4

### Get In Touch

 **Call:** [0845 6880112](tel:08456880112)  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH



## Specification text

### Stylish air curtain for commercial and industrial premises, with intelligent control

- Horizontal mounting
  - Recommended installation height 4,2 m\*
- Vertical mounting
  - Recommended installation width 6 m\*  
(2 units), one on each side

### Application

With air curtain PA4200 there are more opportunities than ever before, packed into the same product. There are therefore many areas of use. PA4200 is specifically designed for doorways in for example, large commercial installations or industrial and warehouse buildings.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

### Design

Through its timeless design and its many accessories, it's easy to get PA4200 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.

## Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

## Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH