



PA4225E30 AIR CURTAIN

Item no. 9994

Document type: **Product card**
 Document date: **2019-07-03**
 Generated by: **Systemair Online Catalogue**

Description

Stylish air curtain for commercial and industrial premises, with intelligent control

- Horizontal mounting
- Recommended installation height 4,2 m*
- Vertical mounting
- Recommended installation width 6 m*
(2 units), one on each side

Application

With air curtain PA4200 there are more opportunities than ever before, packed into the same product. There are therefore many areas of use. PA4200 is specifically designed for doorways in for example, large commercial installations or industrial and warehouse buildings. The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

Design

Through its timeless design and its many accessories, it's easy to get PA4200 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

*) Recommended installation height and width varies depending on the relevant premises.

Technical parameters

Unit	
Type of installation	Horizontal/Vertical
Type of heating	Electrical heat
Length	2549 mm
Height	295 mm
Depth	611 mm
Weight	113 kg
Max. installation height	4200 mm
Color casing	RAL 9016, NCS S 0500-N
Color, outlet grilles	RAL 7046
Protection class	IP20
Ambient working temperature range (dry conditions)	-20-30 °C
Air flow	
Air flow step 5	5900 m³/h
Air flow step 4	5100 m³/h
Air flow step 3	4000 m³/h
Air flow step 2	3000 m³/h
Air flow step 1	2300 m³/h

Get In Touch

Call: [0845 6880112](tel:08456880112)
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





Sound data		
Sound power level LWA	85	dB(A)
Sound level step 5	69	dB(A)
Sound level step 4	65	dB(A)
Sound level step 3	60	dB(A)
Sound level step 2	54	dB(A)
Sound level step 1	49	dB(A)
Control/motor data		
Control/motor supply	230	V
Control/motor current, 50Hz	9,3	A
Max fan rpm	1900	r.p.m.
Motor power 50Hz	2140	W
Heater		
Supply voltage heating	400	V
Phase	3	~
Electric heating 100%	30	kW
Electric heating 66%	20	kW
Electric heating 33%	9,9	kW
Current heating 100%	42,9	A
Current heating 66%	28,6	A
Current heating 33%	14,3	A
Temperature rise, maximum heat output, highest airflow	15	°C
Temperature rise, maximum heat output, lowest airflow	39	°C

Accessories

Accessories


- [SIRERTX Room sensor \(17539\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [PA4XT25 Outlet extension \(19093\)](#)
- [PA34VD30 Vibration damper \(18067\)](#)
- [PA4DW25 Design kit wall \(110841\)](#)
- [PA4JK Vertical kit/Joining kit \(110760\)](#)
- [PA34WB30 Wall brackets \(18046\)](#)
- [PA34WS30 Wire suspension \(18064\)](#)
- [PA4VDW25 Design kit vertical \(110756\)](#)
- [PA34TR30 Threaded Rods \(18058\)](#)
- [PA34CB30 Ceiling Bracket \(18061\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

Name: **PA4225E30 AIR CURTAIN** | Item no.: **9994**

Document type: **Product card** | Document date: **2019-07-03** | Generated by: **Online catalogue**

2 / 3

Get In Touch






 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk


Our Address


Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH





Documentation

-  [ma_frico_pa3500-4200_gb_180926.pdf \(3,49MB\)](#)
-  [ma_frico_PA3JK_PA4JK_PA34VDW_vertical.pdf \(1,53MB\)](#)
-  [ma_frico_PA3XT_PA4XT_150415.pdf \(381,55kB\)](#)
-  [ma_frico_pa34tr_pa34cb-pa34vd.pdf \(739,11kB\)](#)
-  [ma_frico_pa34ws_pa34cb.pdf \(916,13kB\)](#)
-  [ma_pa34jk_pa34dw_horizontal.pdf \(1,74MB\)](#)

-  [cat_frico_ac_sire_valves_gb_20170523.pdf \(345,98kB\)](#)
-  [cat_frico_pa3500_pa4200_gb.pdf \(1,43MB\)](#)

-  [wd_frico_pa4200_gb.pdf \(168,25kB\)](#)

-  [DoC Air curtains_gb 2017-04.pdf \(224,51kB\)](#)

-  [Cad drawings \(dwg\) PA4225E 3D.dwg.dwg \(364,38kB\)](#)
-  [Cad drawings \(dwg\) PA4225E 2D.dwg.dwg \(169,36kB\)](#)

Specification text

Stylish air curtain for commercial and industrial premises, with intelligent control

- Horizontal mounting
 - Recommended installation height 4,2 m*
 - Vertical mounting
 - Recommended installation width 6 m*
- (2 units), one on each side

Application

With air curtain PA4200 there are more opportunities than ever before, packed into the same product. There are therefore many areas of use. PA4200 is specifically designed for doorways in for example, large commercial installations or industrial and warehouse buildings. The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

Design

Through its timeless design and its many accessories, it's easy to get PA4200 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

*) Recommended installation height and width varies depending on the relevant premises.

Get In Touch

-  **Call:** [0845 6880112](tel:08456880112)
-  **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH