



R MAX IN-DUCT PURIFIER

Date:	2020-01-08
Date.	2020 01 00

Project Name				
Architect				
Engineer				
Purchaser				
Submitted by				


Quantity		Unit(s) Designation	RESIDENTIAL IN-DUCT	Model No.:	R MAX
----------	--	---------------------	---------------------	------------	-------

TYPE: RESIDENTIAL PURIFIER

c PS us

STANDARD FEATURES

OTANDARD I LATORES	CERTIFIED
Capacity	up to 4,000 sq ft (375 sq m)
Shipping Weight	10.5 lbs (4.78 kg)
Power	120-240v 50-60 Hz
Watts/Amps	48 Watts/ < 0.5A (Fuse on the board: 2A 250V)
Automatic airflow sensing	Buit-in Thermistor (non activated)
In-duct installation	Return or supply (pivoting tube in 90° increments)
Duct mounting frame	Yes
Line cord	6 ft / 3 prong
Reaction chamber	6 in (15.25 cm) aluminum square tube- photocatalyst cobalt
Electronic display	2" x 5", status, fail signals, countdown to change lamp
UV wavelength in nanometers (nm)	254nm UVC/ 185nm UVV- 1 inch splice
UV lamp configuration	"J" shaped, parallel to the airflow
UV lamp length	10.5 in. (26.6 cm)
Internal lumina lamp coating to prevent solarization	Yes
Lamp change-out	26,304 hours
Lamp warranty	3 years
Ballast warranty	3 years
Access to internal	Front cover held with 4 screws
Construction	Steel/Powder coat paint
Certifications	
Lamp (part number)	LMPHGXJ105
Ballast (part number)	BST120/277GLR





Get In Touch

Our Address

Call: 0845 6880112

Email: info@adremit.co.uk



