



SWT02 FAN HEATER

Item no. 17564

Ceiling mounted fan heater with water heat.

Description

The SWT fan heater is used for heating entrances, stores, industrial premises, workshops, sports halls, garages and shops. The low height means that SWT can also be recessed into a suspended ceiling.

The SWT fan heater has a robust design in white enamelled steel panels. SWT is intended for water connection and is ceiling mounted.

Document type: Product card Document date: 2019-06-19

Generated by: Systemair Online Catalogue

Technical parameters

| Unit | | |
|--|----------------------|-------|
| Type of heating | Water | |
| Width | 705 | mm |
| Height | 330 | mm |
| Depth | 535 | mm |
| Weight | 19 | kg |
| Color casing | RAL 9003, NCS 0500-N | |
| Protection class | IP44 | |
| Air flow | | |
| Air flow step 2 | 1100 | m³/h |
| Air flow step 1 | 700 | m³/h |
| Sound data | | |
| Sound level step 2 | 53 | dB(A) |
| Sound level step 1 | 37 | dB(A) |
| Control/motor data | | |
| Control/motor supply | 230 | V |
| Control/motor current | 0,4 | А |
| Heater | | |
| Max. water temperature | 80 | °C |
| Max. working pressure | 10 | bar |
| Dimension water connections | Ø22 | |
| Water content in coil | 1,2 | I |
| Water heating full output 60/40 °C, air +15 °C | 6,6 | kW |
| Pressure drop water 80/60 °C, air +15 °C | 4,5 | kPa |

Name: SWT02 FAN HEATER | Item no.: 17564

Document type: Product card | Document date: 2019-06-19 | Generated by: Online catalogue



Get In Touch

Call: <u>0845 6880112</u>



Email: info@adremit.co.uk



Accessories

Accessories

RE 1,5 Speed control (5000)

RE 3 Speed control (5001)

RE 7 Speed control (5003)

TVV20 2-way Valve (10638)

CB20 Control Box (10737)

SWTCF02 (17567)

SWTCE02 (17570)

SWTCL02 (17573)


SD20 Actuator (10073)


KRT1900 Thermostat IP55 (5999)

TK10S Electronic Thermostat (24728) T10S Electronic Thermostat (24727)

Documentation















Specification text

Ceiling mounted fan heater with water heat.

Application

The SWT fan heater is used for heating entrances, stores, industrial premises, workshops, sports halls, garages and shops. The low height means that SWT can also be recessed into a suspended ceiling.

Design

The SWT fan heater has a robust design in white enamelled steel panels. SWT is intended for water connection and is ceiling mounted.

Name: SWT02 FAN HEATER | Item no.: 17564

Get In Touch

Document type: Product card | Document date: 2019-06-19 | Generated by: Online catalogue







2/2