



Technical parameters

Installation	
Type of installation	Vertical
Nominal data	
Color casing	White aluminium
Color casing, RAL	RAL 9006
Enclosure class	IP54
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,050 mm
Height	465 mm
Depth	640 mm
Weight	110 kg
Air flow	
Air flow	2.0278 m³/s
Sound data	
Sound level	60 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m².
Sound power (LWA)	76 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.
Motor/control supply	
Control/motor supply	400 V
Phases, motor	3~
Control/motor current, 50 Hz	1.5 A
Input power (P1), motor 50Hz	650 W
Parameter	
Air flow	2.03 m³/s

Accessories

RTRD 14 Speed cont. Systemair (5944)

RTRD 5.2 Speed control IP54 (32399)

AGB304 Door switch (10016)

RTRD 3 Speed control IP54 (32594)

RTRD 7 speed control Systemair (5943)

Get In Touch



Call: 0845 6880112



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



Documents

Catalogue pages AGI4500 AGI6000

Manual AGI4500 AGI6000

Declaration of Conformity AGI

UKCA Declaration AGI

Article name: AGIVR4520A Air curtain | Product link: <https://shop.systemair.com/en-GB/productPermalink?p=110804> | Item Number: 88409 | Document type: Product card | Created at: 19.02.2024 | Generated by: Systemair Online Catalogue | Language: English

Page 2 of 2

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

