



Technical parameters

Installation	
Type of installation	Vertical
Nominal data	
Color casing	White aluminium
Color casing, RAL	RAL 9006
Enclosure class	IP54
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	3,050 mm
Height	465 mm
Depth	640 mm
Weight	133 kg
Air flow	
Air flow	3.0278 m³/s
Sound data	
Sound level	62 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m².
Sound power (LWA)	78 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.
Motor/control supply	
Control/motor supply	400 V
Phases, motor	3~
Control/motor current, 50 Hz	2.2 A
Input power (P1), motor 50Hz	980 W
Parameter	
Air flow	3.03 m³/s

Accessories

RTRD 14 Speed cont. Systemair (5944)

RTRD 5.2 Speed control IP54 (32399)

AGB304 Door switch (10016)

RTRD 3 Speed control IP54 (32594)

RTRD 7 speed control Systemair (5943)

Get In Touch



Call: 0845 6880112



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



Documents

Catalogue pages AGI4500 AGI6000

Manual AGI4500 AGI6000

UKCA Declaration AGI

Article name: AGIVR4530A Air curtain | Product link: <https://shop.systemair.com/en-GB/productPermalink?p=111663> | Item Number: 88411 | Document type: Product card | Created at: 19.02.2024 | Generated by: Systemair Online Catalogue | Language: English

Page 2 of 2

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH

