



Technical parameters

Installation		
Type of installation	Horizontal	
Recommended installation height	3.2 m	
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30 °C	
Dimensions and weights		
Length	1,078	mm
Height	256	mm
Depth	475	mm
Weight	30	kg
Air flow		
Air flow	0.5; 0.375; 0.2778 m ³ /s	
Sound data		
Sound level	57; 50; 43 dB(A)	
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .	
Sound power (LWA)	73 dB(A)	
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.	
Motor/control supply		
Control/motor supply	230	V
Control/motor current	0.7	A
Input power (P1), motor	168	W

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





Electric heat		
Current heating	13; 8.7	A
Voltage heating	230	V
Input power, heater	3; 2	kW
Phases	1~	
Temperature rise, maximum heat output, highest airflow	5	°C
Temperature rise, maximum heat output, lowest airflow	9	°C
Others		
Heat output	3	kW

Parameter	
Output	3.00 kW
Air flow	0.50 m³/s
Inlet air temperature	20.0 °C
Outlet air temperature	25.0 °C
Inlet air humidity	70 % r.H
Outlet air humidity	52 % r.H

Accessories

PA2DR Remote + door contact (15662)

PA34TR15 Threaded bars (18056)

PAMLK PC board alarm (18690)

PA34CB15 Ceiling brackets (18059)

PA34VD15 Vibration damper (18065)

Documents

Catalogue pages AR3200C

Manual AR3200C

AR3210 2D.dwg

AR3210 3D.dwg

AR3210 3D.dxf

Declaration of Conformity AR3200C

UKCA Declaration AR3200C

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH