



## Technical parameters

Installation		
Type of installation	Horizontal	
Recommended installation height	3.2 m	
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP21	
Ambient working temperature (dry conditions)	-20 to 30 °C	
Dimensions and weights		
Length	1,588	mm
Height	256	mm
Depth	475	mm
Weight	40	kg
Air flow		
Air flow	0.8056; 0.5833; 0.4444 m <sup>3</sup> /s	
Sound data		
Sound level	57; 50; 43 dB(A)	
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m <sup>2</sup> .	
Sound power (LWA)	73 dB(A)	
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.	
Motor/control supply		
Control/motor supply	230 V	
Phases, motor	1~	
Control/motor current	1.3 A	
Input power (P1), motor	283 W	
Parameter		
Air flow	0.81 m <sup>3</sup> /s	

### Get In Touch

Call: 0845 6880112  
 Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
 Settle, North Yorkshire, BD24 9RH





## Accessories

PA2DR Remote + door contact (15662)  
PA34TR15 Threaded bars (18056)  
PAMLK PC board alarm (18690)

PA34CB15 Ceiling brackets (18059)  
PA34VD15 Vibration damper (18065)

## Documents

Catalogue pages AR3200C  
Manual AR3200C  
AR3215 2D.dwg  
AR3215 3D.dwg  
AR3215 3D.dxf  
Declaration of Conformity AR3200C  
UKCA Declaration AR3200C

### Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH