



Technical parameters

Installation	
Type of installation	Horizontal
Recommended installation height	3.5 m
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,073 mm
Height	302 mm
Depth	638 mm
Weight	60 kg
Air flow	
Air flow	1.0556; 0.8889; 0.625 m ³ /s
Sound data	
Sound level	63; 59; 45 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .
Sound power (LWA)	79 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



**Motor/control supply**

Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	4.1	A
Input power (P1), motor 50Hz	670	W
Control/motor current, 60 Hz	4.1	A
Input power (P1), motor 60Hz	670	W
Enclosure class, motor	IP20	
Insulation class	B	

Parameter

Air flow	1.06 m³/s
----------	-----------

Accessories

AR35XTT20 Air extension (19072)
 FCDA Control for air curtain (74684)
 FCPA Control for air curtain (74686)
 PA34CB20 Ceiling brackets (18060)
 PA34VD20 Vibration damper (18066)

FCBA Control for air curtain (74687)
 FCOTX Outdoor temp. sensor (74695)
 FCSA Control for air curtain (74685)
 PA34TR20 Threaded bars (18057)

Documents

Catalogue pages Arden 3500
 Manual Arden 3500
 Declaration of Conformity ARFEC3500
 UKCA Declaration ARFEC3500
 Exploded view ARFEC35

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

