



Technical parameters

Installation	
Type of installation	Horizontal
Recommended installation height	3.5 m
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,073 mm
Height	302 mm
Depth	638 mm
Weight	73.3 kg
Air flow	
Air flow	1.0278; 0.8472; 0.5833 m ³ /s
Sound data	
Sound level	61; 57; 45 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .
Sound power (LWA)	77 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.

Get In Touch

Call: 0845 6880112
Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





Motor/control supply		
Control/motor supply	230	V
Phases, motor	1~	
Control/motor current, 50 Hz	4.2	A
Input power (P1), motor 50Hz	680	W
Control/motor current, 60 Hz	4.2	A
Input power (P1), motor 60Hz	680	W
Enclosure class, motor	IP20	
Insulation class	B	

Water data		
Water heating full output 40/30 °C, air +18 °C	16	kW
Pressure drop water 40/30 °C, air +18 °C	5	kPa
Water temperature	5 to 110	°C
Maximum working pressure	1.6	MPa
Water volume inside coil	5.8	L
Dimension water connections	DN20 (G 3/4") Inside thread	

Parameter		
Output	51.68	kW
Air flow	3,700.00	m³/h
Inlet air temperature	20.0	°C
Outlet air temperature	60.8	°C
Water flow	0.631	l/s
Air pressure drop	41	Pa
Inlet air humidity	70	% r.H
Outlet air humidity	7	% r.H
Water pressure drop	10.3	kPa
Inlet fluid temperature	80	°C
Outlet fluid temperature	60	°C
Fluid	Water	

Accessories

AR35XTT20 Air extension (19072)

FCBA Control for air curtain (74687)

FCOTX Outdoor temp. sensor (74695)

FCSA Control for air curtain (74685)

PA34TR20 Threaded bars (18057)

VPFC15LF Valve system (238293)

VPFC20 Valve system (238295)

VPFC32 Valve system (238297)

DTV200S Filter pressure guard (17597)

FCDA Control for air curtain (74684)

FCCA Control for air curtain (74686)

PA34CB20 Ceiling brackets (18060)

PA34VD20 Vibration damper (18066)

VPFC15NF Valve system (238294)

VPFC25 Valve system (238296)

Documents

Catalogue pages Arden 3500

Manual Arden 3500

Declaration of Conformity ARFEC3500

UKCA Declaration ARFEC3500

Exploded view ARFEC35

Article name: ARFEC3520WLL Air curtain Arden | Product link: <https://shop.systemair.com/en-GB/productPermalink?p=531463> | Item Number: 190555 | Document type: Product card | Created at: 19.02.2024 | Generated by: Systemair Online Catalogue | Language: English

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH

