



Technical parameters

Installation	
Type of installation	Horizontal
Recommended installation height	4.2 m
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,577 mm
Height	296 mm
Depth	851 mm
Weight	71 kg
Air flow	
Air flow	1.0139; 0.8611; 0.5417 m ³ /s
Sound data	
Sound level	60; 56; 43 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .
Sound power (LWA)	76 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



**Motor/control supply**

Control/motor supply	230 V
Phases, motor	1~
Control/motor current, 50 Hz	4.1 A
Input power (P1), motor 50Hz	675 W
Control/motor current, 60 Hz	4.1 A
Input power (P1), motor 60Hz	675 W
Enclosure class, motor	IP20
Insulation class	B

Parameter

Air flow	1.01 m³/s
----------	-----------

Accessories

- AR42XTT15 Air extension (88061)
- FCDA Control for air curtain (74684)
- FCSA Control for air curtain (74685)
- PA34TR15 Threaded bars (18056)

- FCBA Control for air curtain (74687)
- FCPA Control for air curtain (74686)
- PA34CB15 Ceiling brackets (18059)
- PA34VD15 Vibration damper (18065)

Documents

- Catalogue pages Arden 4200
- Manual Arden 4200
- Declaration of Conformity ARFEC4200
- UKCA Declaration ARFEC4200
- Exploded view ARFEC42

Get In Touch

- Call: 0845 6880112
- Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH

