



## Technical parameters

Installation	
Type of installation	Horizontal
Recommended installation height	2.5 m
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP21
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	1,560 mm
Height	210 mm
Depth	345 mm
Weight	23 kg
Air flow	
Air flow	0.5833; 0.4722; 0.3472 m <sup>3</sup> /s
Sound data	
Sound level	54; 49; 44 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m <sup>2</sup> .
Sound power (LWA)	71 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.
Motor/control supply	
Control/motor supply	230 V
Phases, motor	1~
Control/motor current	0.7 A
Frequency	50; 60 Hz
Input power (P1), motor	155 W
Parameter	
Air flow	0.58 m <sup>3</sup> /s

### Get In Touch

 **Call:** 0845 6880112  
 **Email:** [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





## Accessories

FCBA Control for air curtain (74687)

FCPA Control for air curtain (74686)

PA2P15 Pendulum bar (19568)

PA34TR15 Threaded bars (18056)

FCDA Control for air curtain (74684)

FCSA Control for air curtain (74685)

PA2PF15 Pendulum brackets (19415)

## Documents

Catalogue pages Pamir 2500

Manual Pamir 2500

Declaration of Conformity PAF2500

UKCA Declaration PAF2500

Exploded view PAF25-32

### Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: [info@adremit.co.uk](mailto:info@adremit.co.uk)

### Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,  
Settle, North Yorkshire, BD24 9RH