




Technical parameters

Installation		
Type of installation	Horizontal	
Recommended installation height	2.5 m	
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP21	
Ambient working temperature (dry conditions)	-20 to 30 °C	
Dimensions and weights		
Length	1,560	mm
Height	230	mm
Depth	345	mm
Weight	26	kg
Air flow		
Air flow	0.5833; 0.4722; 0.3472 m ³ /s	
Sound data		
Sound level	54; 48; 41 dB(A)	
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .	
Sound power (LWA)	70 dB(A)	
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.	
Motor/control supply		
Control/motor supply	230 V	
Phases, motor	1~	
Control/motor current	0.6 A	
Frequency	50; 60 Hz	
Input power (P1), motor	140 W	
Electric heat		
Temperature rise, maximum heat output, highest airflow	13 °C	
Temperature rise, maximum heat output, lowest airflow	16 °C	

Article name: PAF2515W Air curtain Pamir | Product link: <https://shop.systemair.com/en-GB/productPermalink?p=545481> | Item Number: 246829 | Document type: Product card | Created at: 19.02.2024 | Generated by: Systemair Online Catalogue | Language: English

Get In Touch

 **Call:** 0845 6880112
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH

**Water data**

Water heating full output 60/40 °C, air +18 °C	9.2	kW
Pressure drop water 80/60 °C, air +18 °C	14	kPa
Pressure drop water 60/40 °C, air +18 °C	5.4	kPa
Water temperature	max 110	°C
Maximum working pressure	1.6	MPa
Water volume inside coil	1.1	L
Dimension water connections	15 mm	Cu

Parameter

Output	15.69	kW
Air flow	2,100.00	m³/h
Inlet air temperature	20.0	°C
Outlet air temperature	41.9	°C
Water flow	0.192	l/s
Air pressure drop	18	Pa
Inlet air humidity	70	% r.H
Outlet air humidity	20	% r.H
Water pressure drop	13.2	kPa
Inlet fluid temperature	80	°C
Outlet fluid temperature	60	°C
Fluid		Water

Accessories

FCBA Control for air curtain (74687)
 FCPA Control for air curtain (74686)
 FHDN15 Flexible hose kit (77179)
 PA2P15 Pendulum bar (19568)
 PA34TR15 Threaded bars (18056)
 VPFC15LF Valve system (238293)
 VPFC20 Valve system (238295)
 VPFC32 Valve system (238297)

FCDA Control for air curtain (74684)
 FCSA Control for air curtain (74685)
 PA2EF15 External intake filter (14876)
 PA2PF15 Pendulum brackets (19415)
 PAWAK15 Quick pipe connections (27279)
 VPFC15NF Valve system (238294)
 VPFC25 Valve system (238296)

Documents

Catalogue pages Pamir 2500
 Manual Pamir 2500
 Declaration of Conformity PAF2500
 UKCA Declaration PAF2500
 Exploded view PAF25-32

Get In Touch

Call: 0845 6880112
Email: info@adremmit.co.uk

Our Address

Puravent, Adremmit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

