



Technical parameters

Installation	
Type of installation	Horizontal & Vertical
Recommended installation height	3.5 m
Nominal data	
Color casing	Traffic white
Color casing, RAL	RAL 9016
Color, outlet grilles	Telegrey 2
Color outlet grilles, RAL	RAL 7046
Enclosure class	IP20
Ambient working temperature (dry conditions)	-20 to 30 °C
Dimensions and weights	
Length	2,039 mm
Height	270 mm
Depth	525 mm
Weight	70 kg
Air flow	
Air flow	0.9722; 0.7778; 0.5278 m ³ /s
Sound data	
Sound level	64; 59; 47 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .
Sound power (LWA)	80 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.
Motor/control supply	
Control/motor supply	230 V
Phases, motor	1~
Control/motor current, 50 Hz	4.1 A
Input power (P1), motor 50Hz	670 W
Control/motor current, 60 Hz	4.1 A
Input power (P1), motor 60Hz	670 W

Get In Touch

 **Call:** 0845 6880112
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



Electric heat		
Current heating	23.4; 15.9; 7.7	A
Voltage heating	400	V
Input power, heater	16.2; 11; 5.4	kW
Phases	3~	
Temperature rise, maximum heat output, highest airflow	14	°C
Temperature rise, maximum heat output, lowest airflow	25	°C

Parameter	
Output	16.20 kW
Air flow	0.97 m³/s
Inlet air temperature	20.0 °C
Outlet air temperature	33.9 °C
Inlet air humidity	70 % r.H
Outlet air humidity	31 % r.H

Accessories

[AXP300 Hit protection \(10028\)](#)
[FCDA Control for air curtain \(74684\)](#)
[FCSA Control for air curtain \(74685\)](#)
[PA34TR20 Threaded bars \(18057\)](#)
[PA34WB20 Wall brackets \(18045\)](#)
[PA3DCL Design kit ceiling \(13555\)](#)
[PA3DCS Design kit ceiling \(13552\)](#)
[PA3DXT Design kit ceiling \(13556\)](#)
[PA3VDW20 Design kit vertical \(110752\)](#)

[FCBA Control for air curtain \(74687\)](#)
[FCPA Control for air curtain \(74686\)](#)
[PA34CB20 Ceiling brackets \(18060\)](#)
[PA34VD20 Vibration damper \(18066\)](#)
[PA34WS20 Wire suspension \(18063\)](#)
[PA3DCM Design kit ceiling \(13553\)](#)
[PA3DW20 Design kit wall \(110836\)](#)
[PA3JK Vertical kit/Joining kit \(110759\)](#)
[PA3XT20 Outlet extension \(19087\)](#)

Documents

[Catalogue pages Pamir 3500](#)
[Manual Pamir 3500/4200/5000](#)
[Declaration of Conformity PAFEC3500](#)
[UKCA Declaration PAFEC3500](#)
[Exploded view PAFEC35-42-50](#)

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremmit.co.uk

Our Address

Puravent, Adremmit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

