



Technical parameters

Installation		
Type of installation	Horizontal	
Recommended installation height	5 m	
Nominal data		
Color casing	Traffic white	
Color casing, RAL	RAL 9016	
Color, outlet grilles	Telegrey 2	
Color outlet grilles, RAL	RAL 7046	
Enclosure class	IP20	
Ambient working temperature (dry conditions)	-20 to 30 °C	
Dimensions and weights		
Length	1,039	mm
Height	295	mm
Depth	611	mm
Weight	46.22	kg
Air flow		
Air flow	0.8194; 0.6667; 0.25 m ³ /s	
Sound data		
Sound level	66; 60; 34 dB(A)	
Sound pressure (LpA)	Conditions: Distance to the unit 5 metres. Directional factor: 2. Equivalent absorption area: 200 m ² .	
Sound power (LWA)	80 dB(A)	
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.	
Motor/control supply		
Control/motor supply	230	V
Control/motor current, 50 Hz	4.4	A
Input power (P1), motor 50Hz	710	W
Frequency	50; 60	Hz
Input power (P1), motor 60Hz	710	W

Article name: PAFEC5010E12 Air curtain Pamir | Product link: <https://shop.systemair.com/en-GB/productPermalink?p=544792> | Item Number: 230376 | Document type: Product card | Created at: 19.02.2024 | Generated by: Systemair Online Catalogue | Language: English

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH





Electric heat		
Current heating	16.9; 11.3; 5.6	A
Voltage heating	400	V
Input power, heater	12; 7.8; 3.9	kW
Phases	3~	
Temperature rise, maximum heat output, highest airflow	12	°C
Temperature rise, maximum heat output, lowest airflow	40	°C

Parameter	
Output	12.00 kW
Air flow	0.82 m³/s
Inlet air temperature	20.0 °C
Outlet air temperature	32.2 °C
Inlet air humidity	70 % r.H
Outlet air humidity	34 % r.H

Accessories

[AXP300 Hit protection \(10028\)](#)
[FCDA Control for air curtain \(74684\)](#)
[FCSA Control for air curtain \(74685\)](#)
[PA34TR15 Threaded bars \(18056\)](#)
[PA34WB15 Wall brackets \(18044\)](#)
[PA4DCL Design kit ceiling \(13560\)](#)
[PA4DCS Design kit ceiling \(13557\)](#)
[PA4DXT Design kit ceiling \(13561\)](#)
[PA4XT10 Outlet extension \(19090\)](#)

[FCBA Control for air curtain \(74687\)](#)
[FCPA Control for air curtain \(74686\)](#)
[PA34CB15 Ceiling brackets \(18059\)](#)
[PA34VD15 Vibration damper \(18065\)](#)
[PA34WS15 Wire suspension \(18062\)](#)
[PA4DCM Design kit ceiling \(13559\)](#)
[PA4DW10 Design kit wall \(110838\)](#)
[PA4JK Vertical kit/Joining kit \(110760\)](#)

Documents

[Catalogue pages Pamir 5000](#)
[Manual Pamir 3500/4200/5000](#)
[Declaration of Conformity PAFEC5000](#)
[UKCA Declaration PAFEC5000](#)
[Exploded view PAFEC35-42-50](#)

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremmit.co.uk

Our Address

Puravent, Adremmit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

