



Technical parameters

Nominal data		
Color casing		Traffic white
Color casing, RAL		RAL 9016
Enclosure class		IP44
Ambient working temperature (dry conditions)		-20 to 30 °C
Dimensions and weights		
Width		478 mm
Height		576 mm
Depth		545 mm
Weight		25 kg
Air flow		
Air flow		2,300 m³/h
Sound data		
Sound level		62; 51 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 3 metres. Directional factor: 2. Equivalent absorption area: 200 m².	
Sound power (LWA)		78 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.	
Motor/control supply		
Control/motor supply		230 V
Phases, motor		1~
Input power (P1), motor		150 W
Electric heat		
Current heating		29.5 A
Voltage heating		400 V
Input power, heater		20; 10 kW
Phases		3N~
Temperature rise, maximum heat output, highest airflow		21 °C
Temperature rise, maximum heat output, lowest airflow		27 °C

Article name: PNF20 Fan Heater Panther FC | Product link: <https://shop.systemair.com/en/productPermalink?p=1329569> | Item number: 334031 | Document type: Product card | Created at: 2024-02-13 | Generated by: Systemair Online Catalogue | Language: English

Get In Touch

Call: 0845 6880112
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard, Settle, North Yorkshire, BD24 9RH



Accessories

FCBF Control for fan heater (74691)

FCPF Control for fan heater (74690)

PLR30 Air director (10275)

FCDF Control for fan heater (74688)

FCSF Control for fan heater (74689)

Documents

Catalogue pages Panther FC 20-30

Manual Panther FC 20-30

Declaration of Conformity Panther FC

UKCA Declaration Panther FC

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH