



# **TSF-250**

Item no. 18673

Document type: **Product card**Document date: **2019-05-29** 

Generated by: Systemair Online Catalogue

# Description

## Technical details can be found here

#### Decsription

TSF perforated exhaust diffuser for ceiling installation.

#### Function

TSF is a perforated exhaust air diffuser designed for ceiling assembly. Plenum box THOR or iris damper SPI should be used to regulate the air flow.

#### Design

TSF is available in 7 different sizes 100-400, size 250-400 do not need adapter plates for installation in suspended ceiling. TSF consists of perforated front plate and a diffuser box, manufactured of sheet metal. The diffuser box has a connection sleeve fitted with a rubber seal. TSF is painted with a white powder coated finish (RAL 9010-80). The front plate is removable to easy access to the duct.

## Mounting

When mounting, pull the perforated front straight out. Connect the diffuser box with blind rivets and then remount the front. If the diffuser is fitted to a THOR plenum box there must be a straight length, 4 times the duct diameter in front of the THOR plenum box. A Sinus P600 is a replacement for a false ceiling tile when installing TSF 100-200. TSF 250400 can be installed directly. The hole dimension is according to the measuring table.



Name: **TSF-250** | Item no.: **18673** 

Document type: Product card | Document date: 2019-05-29 | Generated by: Online catalogue



**Get In Touch** 

**Call:** 0845 6880112

Email: info@adremit.co.uk