



TSP-250

Item no. 19957

Document type: **Product card**

Document date: **2019-05-29**

Generated by: **Systemair Online Catalogue**

Description

Description

Systemair TSP ceiling diffuser complete with plenum box for visible installation. The plenum box is fitted with test points and fibre-free sound insulation.

Function

The TSP is a complete circular perforated supply diffuser, with an adjustable diffuser unit combined with a plenum box. The plenum box has a damper and test points, and is internally lined with fibre-free sound-insulation material. The TSP is suitable for cooled air with a maximum dT of 12 K.

Design

The TSP is manufactured from sheet metal with a white powder-coated finish (RAL 9010-80) and is available in the following diameters: \varnothing 100, \varnothing 125, \varnothing 160, \varnothing 200 and \varnothing 250.

How to use for exhaust air

This device can be used for exhaust air as explained in printed catalogue.

Mounting

The diffuser is fixed securely by screwing up into the ceiling from the inside of the unit. The front plate can be removed by pulling it straight out. The sound-absorbing material is cut out of the diffuser's centre to make room for the screws. TSP has a M8 blind rivet for suspension.

Technical details can be found [here](#)



Specification text

Get In Touch



Call: [0845 6880112](tel:08456880112)



Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
Settle, North Yorkshire, BD24 9RH