



VBR 50-25-4 WATER HEATING BATT

Item no. 5472

Document type: **Product card**
 Document date: **2019-05-15**
 Generated by: **Systemair Online Catalogue**

Description

Water-heating battery

Water-heating battery for heating air in ventilation systems with rectangular ducts. Hot-zinc-coated casing, heat transmission element with copper tubes and aluminium fins. In cold conditions, a frost protection device with sensor should be fitted to reduce the risk of damage from freezing. The water-heating battery can be installed in a horizontal or vertical duct with an optional direction.



Technical parameters


Max. operating temperature	150	°C
Max. operating pressure, at water temp. 100°C	1600000 (16bar)	Pa
Max. operating pressure, at water temp. 150°C	1000000 (10bar)	Pa

Accessories

Electric accessories

- [ZTR 20-4.0 valve 3-way \(9678\)](#)
- [AQUA 24TF Heat Regulator \(5136\)](#)
- [TG-A130 Surface sensor 0-30°C \(5159\)](#)
- [TG-K330 Duct Sensor 0-30°C \(5160\)](#)
- [TG-D1/PT1000 Immersion sensor \(6773\)](#)
- [RVAZ4-24 Actuator 3points \(9798\)](#)
- [ZTV 20-4.0 2-way valve \(9826\)](#)
- [RVAZ4 24A Actuator 0-10V \(9862\)](#)

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk


Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

Dimensions

VBR XX-XX-2 = Two pipe rows
 VBR XX-XX-4 = Four pipe rows
 VBR XX-XX-3 = Three pipe rows

F= Thread G 1/4
 G= Airing
 H= Water out
 I= Connection for immersion sensor
 J= Water in
 K= Draining





	A	c/c A	B	c/c B	E	
VBR 40-20-2	438	420	238	220	R 3/4"	5.5 kg
VBR 50-25-2	538	520	288	270	R 3/4"	7 kg
VBR 50-30-2	538	520	338	320	R 3/4"	8 kg
VBR 60-30-2	638	620	338	320	R 3/4"	9 kg
VBR 60-35-2	638	620	388	370	R 3/4"	10 kg
VBR 70-40-2	738	720	438	420	R 1"	12.5 kg
VBR 80-50-2	838	820	538	520	R 1"	16 kg
VBR 100-50-2	1038	1020	538	520	R 1"	18.5 kg

	A	c/c A	B	c/c B	E	
VBR 40-20-4	438	420	238	220	R 3/4"	7 kg
VBR 50-25-4	538	520	288	270	R 3/4"	9 kg
VBR 50-30-4	538	520	338	320	R 1"	10.5 kg
VBR 60-30-4	638	620	338	320	R 1"	11.5 kg
VBR 60-35-4	638	620	388	370	R 1"	13 kg

	A	c/c A	B	c/c B	E	
VBR 70-40-3	738	720	438	420	R 1"	15.5 kg
VBR 80-50-3	838	820	538	520	R 1"	19 kg
VBR 100-50-3	1038	1020	538	520	R 1"	22.5 kg

Documentation

 VBR_172010.PDF (503,91kB)

 Conformity_decl. PGK_VBR(PGV)_VBC(CWW)_CWK.pdf (17,06kB)

Coil calculation

Name: **VBR 50-25-4 WATER HEATING BATT** | Item no.: **5472**

Document type: **Product card** | Document date: **2019-05-15** | Generated by: **Online catalogue**

2 / 2

Get In Touch

 Call: [0845 6880112](tel:08456880112)
 Email: info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH