



VBR 50-30-4 WATER HEATING BATT

Item no. 5473

Document type: **Product card**
 Document date: **2019-05-15**
 Generated by: **Systemair Online Catalogue**


Description

Water-heating battery

Water-heating battery for heating air in ventilation systems with rectangular ducts. Hot-zinc-coated casing, heat transmission element with copper tubes and aluminium fins. In cold conditions, a frost protection device with sensor should be fitted to reduce the risk of damage from freezing. The water-heating battery can be installed in a horizontal or vertical duct with an optional direction.



Documentation

 [VBR IMO_172010.pdf \(636,16kB\)](#)

 [Conformity_decl. PGK_VBR\(PGV\)_VBC\(CWW\)_CWK.pdf \(17,06kB\)](#)

Technical parameters

Max. operating temperature	150	°C
Max. operating pressure, at water temp. 100°C	1600000	Pa
Max. operating pressure, at water temp. 150°C	1000000	Pa


Coil calculation

Accessories

Electric accessories

- [ZTR 20-4.0 valve 3-way \(9678\)](#)
- [AQUA 24TF Heat Regulator \(5136\)](#)
- [TG-A130 Surface sensor 0-30°C \(5159\)](#)
- [TG-K330 Duct Sensor 0-30°C \(5160\)](#)
- [TG-D1/PT1000 Immersion sensor \(6773\)](#)
- [RVAZ4-24 Actuator 3points \(9798\)](#)
- [ZTV 20-4.0 2-way valve \(9826\)](#)
- [RVAZ4 24A Actuator 0-10V \(9862\)](#)

Get In Touch

 **Call:** [0845 6880112](tel:08456880112)
 **Email:** info@adremit.co.uk

Our Address

Puravent, Adremit Limited, Unit 5a, Commercial Yard,
 Settle, North Yorkshire, BD24 9RH

