FC Smart Fan Heater Controls Heaters

FC Smart – Second level control system for full freedom

- Automatic fan speed control
- Control via app (Bluetooth)
- Wireless sensors possible
- Adjustable calendar function
- Away, Boost and Presence function
- Zone possibility
- Enhanced water control possible
- Built-in temperature sensor
- Outlet temperature limit

Find more details in our online catalogue

Control with App

The Frico app with its user-friendly interface makes it easy to set up and control products directly from your smartphone or tablet, allowing you to control your comfort with ease. The app FRICO CONTROL is available for both iOS and Android.

Create Zones

The zone feature allows you to create different zones for different conditions in a larger system, to create maximum comfort and energy savings in all areas. All zones can be controlled from the same app.

Wireless sensors offer easier installations

Indoor and outdoor temperatures can be measured by wireless sensors, which allows for quicker and easier installations as no preparatory work is needed to connectcables through walls. Applies to FCTXRF, indoor/outdoor wireless sensor.

Enhanced Water control

Water heat is more accurate controlled with improved water functions and modulating actuators. Automatic functions such as bypass, frost protection and return water temperature control (with sensor FCWTA) improve product functionality without any additional effort.

FC Smart comes with all features from FC Direct plus additional energy saving features and the possibility of app control (Bluetooth). The app gives you access to all functions in the system, allowing you to set it up exactly the way you want it. It also enables you to create different zones with different settings in a larger system. Choose between several modes for heating only when needed, such as Away, Boost and Presence. The app FRICO CONTROL is available for both iOS and Android.

Content

- FCCF control panel with built-in temperature sensor
- FCBC10 communication cable, 10 m
- FCLAP local access point Bluetooth

In addition to the package, components can be added to expand and customize the system. Added zones needs to be equipped with one FC Direct and can be designed to fit its specific needs by adding different components. Please see accessories.

Technical parameters

Nominal data	
Enclosure class	IP44

Dimensions and weights		
Weight	0.1	kg

Accessories

- FCBC05 Communication cable (74718)
- FCBC25 Communication cable (74720)
- FCOTX Outdoor temp. sensor (74695)
- FCSC10 Sensor cable (74721)
- FCTXRF Wireless temp sensor (74703)

- FCBC10 Communication cable (74719)
- FCLAP Com. unit for app (74699)
- FCRTX Ext. room sensor (74694)
- FCSC25 Sensor cable (74722)
- FCWTA Water temp sensor (74702)

Documents

- Catalogue pages FC for fan heaters
- Quickguide Frico Control FH - FCSF FCDF FCPF FCBF
- Declaration of Conformity FC
- UKCA Declaration FC