

## Panther T Wall Mounted Fan Heaters

### Powerful fan heater for technical heating

- Compact with high output
- Easy mounting with flexible wall bracket
- Long service life
- For installations not covered by the Ecodesign Regulation

[Find more details in our online catalogue.](#)



### Protects your equipment

Panther T is an efficient fan heater for stationary use that provides fast and effective heating for your technical environments. The investment in Panther T is minor compared to potentially high damage costs caused by frost or humidity.

### Compact and Robust

Panther T is a powerful and robust fan heater with a long service life. The fan heater is easy to install and requires a minimum of maintenance, which reduces costs and the risk of errors.

### External Control

Panther T must be supplemented with an external control panel PP. It provides easy operation and can control multiple units simultaneously. The fan heater should be installed with an external thermostat. Thermostat controls are available as accessories.

### Versatile Wall bracket

Supplied with a versatile wall bracket that makes it possible to direct the airflow where it's needed, downwards and to the side.

Panther T is a series of efficient fan heaters designed for drying and heating installations of a more technical nature. Panther T is suitable in, for example, service areas, utility rooms and drying rooms.

Panther is mounted on the wall and comes with a wall bracket that makes it possible to direct the air flow downwards and to the side (30° left or right).

Panther T must be supplemented with a control panel PP. Up to 6 units can be controlled by one control panel. PNT135 requires one PP15N per unit. The fan heater should be installed with an external thermostat.

## Technical parameters

### Nominal data

Color casing	Grey
Color casing, RAL	RAL 7046
Enclosure class	IP44
Ambient working temperature (dry conditions)	-20 to 30 °C

### Dimensions and weights

Width	450 mm
Height	520 mm
Depth	510 mm
Weight	22 kg

### Air flow

Air flow	1300; 900 m <sup>3</sup> /h
----------	-----------------------------

### Sound data

Sound level	31; 23 dB(A)
Sound pressure (LpA)	Conditions: Distance to the unit 3 metres. Directional factor: 2. Equivalent absorption area: 200 m <sup>2</sup> .
Sound power (LWA)	61 dB(A)
Conditions sound level	Measurements according to ISO 27327-2: 2014, Installation type E.

### Motor/control supply

Control/motor supply	230 V
Phases, motor	1~
Input power (P1), motor	70 W

### Electric heat

Current heating	21.7 A
Voltage heating	400 V
Input power, heater	15; 7.5 kW
Phases	3N~
Temperature rise, maximum heat output, highest airflow	35 °C
Temperature rise, maximum heat output, lowest airflow	50 °C

### Others

Heat output	15 kW
-------------	-------

## Accessories

- KRT2800 Capillary thermostat (5989)
- PP15N Control box (94730)
- RTI2 Electronic thermostat (10231)
- PLR15 Air director (10274)
- PTA01 Temperature control (10281)

## Documents

- Catalogue pages Panther T
- Manual Panther T
- Declaration of Conformity Panther T
- UKCA Declaration Panther T